

MDC (M12) Series Field Wireable Plugs

4, 5 & 8 Conductor MDC Series Field Wireable Plugs, 18-24/20-24AWG



Straight Field Wireable Plugs

Shielded

IP67 Rating









# of Poles	Male Faceview	Rating	Wire AWG	Cable 0.D. Range	Part Number	
					Male Plugs	Female Plugs
4	20 30 01 04 M12 x 1	250V 4A	18-24 AWG	3-9 mm	MDCM-4MP-FW	MDCM-4FP-FW
5	20 30 0 ⁵ 01 0 ₄ M12 x 1	125V 4A	18-24 AWG	3-9 mm	MDCM-5MP-FW	MDCM-5FP-FW
8	30 20 0 80 01 4 70 05 06 M12 x 1	60V 2A	20-24AWG	6-8 mm	MDCM-8MP-FW	MDCM-8FP-FW

These connectors are easily wired by inserting the individual wires into the screw terminal contacts. The connectors are water tight to IP 67 and are fully mateable with other "Micro DC" style connectors.


4 & 5 Pole Version

Male Straight



Female Straight

8 Pole Version



Male Straight



Female Straight



Specifications:

Body: Nickel Plated Brass Insulator: Black Polyamide

Contacts: Copper Alloy with Gold Plating

Coupling Nut: Nickel Plated Brass

Seal: NBR

Temperature: -25°C to $+85^{\circ}\text{C}$ (-13°F to $+185^{\circ}\text{F}$)

H-38 M

Mencom Corporation

1-770-534-4585

www.mencom.com