



MDC (M12) Series Cordsets

4 Conductor MDC Series Cordsets, 22AWG





Double Ended Cordsets | Straight | 300 Volt, 4 amps | IP69 Rating



H

Micro-DC (M12) Series Cordsets


Male Faceview	Part Number	Cables	Features	Color Code	Female Faceview
 <p>M12 x 1</p>	MDCP-4MFP-**	Yellow PUR AWM 4 X 22 AWG 300V, 4A -40°C to +80°C 5mm OD	Oil and Cutting Fluid Resistant Cut Resistant PUR	<p>1. Brown 2. White 3. Blue 4. Black</p>	 <p>M12 x 1</p>
	MDCPQ-4MFP-**	Yellow PUR AWM 4 X 22 AWG 300V, 4A -40°C to +80°C 5mm OD	Coiled Oil and Cutting Fluid Resistant Cut Resistant PUR		
	MDCW-4MFP-**	Yellow TPE AWM 4 X 22 AWG 300V, 4A -40°C to +80°C 5mm OD	Weld Slag Resistant TPE		
	MDCWF-4MFP-**	Black TPE AWM 4 X 22 AWG 300V, 4A -40°C to +105°C 5mm OD	Hi-Flex Weld Slag Resistant TPE		

** Lengths in meters. Standard cable lengths are 1, 2, 4, 5, 6, 10 & 15 meters. Consult factory for other lengths.


Females will have all 5 contact holes in the connector.

Black and gray cables are available on some versions, please consult the factory.

Standard coupling nut is nickel plated brass, for stainless steel coupling nut add a "-SS" suffix. (e.g. MDCP-4MFP-1M becomes MDCP-4MFP-1M-SS)



Male - Female Extension



Male - Female Coiled Extension