



Ethernet (M12) Series Etherplug Cordsets

8 Conductor Ethernet Series Cordsets, 24/26AWG



Straight Male Cordsets | 60 Volt, 2 amps | CAT5e | A-Coded | Twisted Pairs | IP67 Rating



Ethernet Series

L



Connector Body Style	Part Number	Cables	Features	Color Code	Faceview
	MDE45-8MP-**	Teal PVC AWM 8 X 24 AWG 60V, 2A -20°C to +80°C 6.4mm OD	Industry Standard PVC		
	MDE45B-8MP-**	Teal PVC AWM With Foil & Braided Shield 8 X 24 AWG 60V, 2A -20°C to +80°C 7.6mm OD	Industry Standard PVC Foil & Braided Shield		
	MDE45P-8MP-**	Teal PUR AWM 8 X 24 AWG 60V, 2A -40°C to +80°C 6.3 mm OD	Continuous-Flex Oil and Cutting Fluid Resistant Cut Resistant PUR		
	MDE45PB-8MP-**	Teal PUR With Foil & Braided Shield 8 X 26 AWG 60V, 2A -40°C to +75°C 6mm OD	Continuous-Flex Oil and Cutting Fluid Resistant Cut Resistant PUR Foil & Braided Shield	1. White/Blue 2. White/Brown 3. Brown 4. Orange 5. White/Green 6. White/Orange 7. Blue 8. Green	 M12 x 1
	MDE45PB-8MSP-**	Teal PUR With Foil & Braided Shield 8 X 26 AWG 60V, 2A -40°C to +75°C 6mm OD	Oil and Cutting Fluid Resistant Cut Resistant PUR Foil & Braided Shield to Coupling Nut		
	MDE45WB-8MP-**	Teal TPE AWM With Foil & Braided Shield 8 X 24 AWG 60V, 2A -40°C to +80°C 7.6mm OD	Continuous-Flex Weld Slag Resistant TPE Foil & Braided Shield		
	MDE45WB-8MSP-**	Teal TPE AWM With Foil & Braided Shield 8 X 24 AWG 60V, 2A -40°C to +80°C 7.6mm OD	Continuous-Flex Weld Slag Resistant TPE Foil & Braided Shield to Coupling Nut		

** Lengths in meters. Standard cable lengths are 1, 2, 4, 5, 6, 10 & 15 meters. Consult factory for other lengths.

Standard coupling nut is nickel plated brass, for stainless steel coupling nut add a "-SS" suffix. (e.g. MDE45-8MP-1M becomes MDE45-8MP-1M-SS)