

Product data sheet

Characteristics

1.5S46F

TRFMR DRY 1PH 1.5KVA 120X240V-16/32V

Product availability : Stock - Normally stocked in distribution facility



Price* : 830.00 USD



Main

Product	Buck and Boost Transformer
Enclosure Code	8A
Enclosure Type	NEMA 3R
Insulation Temperature	356 °F (180 °C)
Primary Voltage	120 x 240 V
Power Rating	1.5 kVA
Secondary Voltage	16/32 V
Temperature Rise	115 °C

Ordering and shipping details

Category	16265 - BUCK & BOOST
Discount Schedule	PE2
GTIN	00785901876458
Nbr. of units in pkg.	1
Package weight(Lbs)	38.24 lb(US) (17.345 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	9.70 in (24.638 cm)
Package 1 width	11.00 in (27.94 cm)
Package 1 Length	12.50 in (31.75 cm)

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------