

Product data sheet

Characteristics

30T2FSS

TRANSFORMER DRY 3PH 30KVA

480V-208Y/120V

Product availability : Non-Stock - Not normally stocked in distribution facility



Price* : 13,022.00 USD



Main

Product or component type	Dry Sealed Transformer
Primary to Secondary Voltage	480 V delta 208Y/120 V
Full Capacity Taps	2.5 % FCBN

Complementary

Enclosure Code	16C
Phase	3 phase
Power Rating	30 kVA
Temperature rise	115 °C
Height	22 in (558.80 mm)
Width	25 in (635.00 mm)
Depth	13.5 in (342.90 mm)
Enclosure mounting	Wall mounted
Enclosure material	Stainless Steel

Environment

Enclosure Type	NEMA 3R
Insulation temperature	356 °F (180 °C)
Product certifications	CULus CSA UL Listed

Ordering and shipping details

Category	16277 - RESIN LVGP XFMR
Discount Schedule	PE2

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Jul 30, 2021

GTIN	00785901015376
Nbr. of units in pkg.	1
Package weight(Lbs)	775 lb(US) (351.53 kg)
Returnability	No
Country of origin	US

Packing Units

Package 1 Height	16.40 in (41.656 cm)
Package 1 width	25.50 in (64.770 cm)
Package 1 Length	21.30 in (54.102 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
RECh Regulation	RECh Declaration
RECh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------