Product data sheet Characteristics

500SV1B XFMR DRY 1PH .5KVA 240X480V-120/240V

Product availability: Stock - Normally stocked in distribution facility





Price*: 386.00 USD



Main

Product or component type	Dry Sealed Transformer
Primary to Secondary Voltage	240 x 480 V 120/240 V
Full Capacity Taps	0

Complementary

Enclosure Code	5A	<u> </u>
Phase	1 phase	
Power Rating	0.5 kVA	<u></u>
Temperature rise	80 °C	
Height	5.5 in (139.70 mm)	tet en
Width	6.19 in (157.23 mm)	
Depth	4.69 in (119.13 mm)	
Enclosure mounting	Wall mounted	
Enclosure material	Painted sheet steel	to be
-	· · · ·	·

Environment

Enclosure Type	NEMA 3R	
Insulation temperature	266 °F (130 °C)	
Product certifications	CULus CSA UL Listed	

Ordering and shipping details

Category	16277 - RESIN LVGP XFMR
Discount Schedule	PE2
GTIN	00785901019831

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Nbr. of units in pkg.	1	
Package weight(Lbs)	15.25 lb(US) (6.917 kg)	
Returnability	Yes	
Country of origin	MX	

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	6.19 in (15.723 cm)
Package 1 width	6.19 in (15.723 cm)
Package 1 Length	4.69 in (11.913 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty 18 months
