

Product data sheet

Characteristics

8903SPG1V03

Contactor, Type S, multipole lighting, electrically held, 60A, 2 pole, 220/240 VAC 50/60 Hz coil, NEMA 1

Product availability : Non-Stock - Not normally stocked in distribution facility



Main

Product	Electrically Held Lighting Contactor
Type	S

Complementary

Control Circuit Voltage	240 V AC 60 Hz 220 V AC 50 Hz
Current Rating	60 A
Number of Poles	2P
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Other Options	None
Electrical connection	Lugs
Height	12.68 in (322 mm)
Depth	6.02 in (153 mm)
Width	7.80 in (198 mm)

Environment

Enclosure Type	NEMA 1 painted sheet steel surface none
Product certifications	UL Listed CSA

Ordering and shipping details

Category	21325 - 8903 S (NOT S*C) ELECT.
----------	---------------------------------

Discount Schedule	CP1
GTIN	00785901023913
Nbr. of units in pkg.	1
Package weight(Lbs)	11.05 lb(US) (5.012 kg)
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	12.68 in (32.2 cm)
Package 1 width	7.80 in (19.8 cm)
Package 1 Length	6.02 in (15.3 cm)

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.

Contractual warranty

Warranty	18 months
----------	-----------