

# Product data sheet

## Characteristics

# 8903SPO3V02

Contacteur, Type S, multipole lighting, électriquement maintenu, 60A, 4 pôles, 110/120VAC 50/60Hz bobine, style ouvert

Product availability : Non-Stock - Not normally stocked in distribution facility



Price\* : 1,146.00 USD



### Main

Product	Electrically Held Lighting Contactor
Type	S

### Complementary

Control Circuit Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Current Rating	60 A
Number of Poles	4P
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Other Options	None
Electrical connection	Lugs
Height	5.51 in (140 mm)
Depth	4.92 in (125 mm)
Width	5.59 in (142 mm)

### Environment

Enclosure Type	Not rated (open device) surface none
Product certifications	UL Listed CSA

\* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

## Ordering and shipping details

Category	21325 - 8903 S (NOT S*C) ELECT.
Discount Schedule	CP1
GTIN	00785901455417
Nbr. of units in pkg.	1
Package weight(Lbs)	6.92 lb(US) (3.139 kg)
Returnability	No
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	7.00 in (17.78 cm)
Package 1 width	6.40 in (16.256 cm)
Package 1 Length	9.10 in (23.114 cm)

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Not compliant
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information.

## Contractual warranty

Warranty	18 months
----------	-----------