

Product data sheet

Characteristics

9080LBA363104

Power distribution block, Linergy, 3 pole, 1 line, 4 load, 335A CU, 270A AL, 600 V

Product availability : Stock - Normally stocked in distribution facility



Price* : 113.00 USD



Main

Range	9080LB
Product	Power Distribution Block
Current Rating	335 A copper 270 A aluminium
Short Circuit Current Rating	65 kA

Complementary

Voltage Rating	600 V AC/DC
Mounting Type	Surface mount
Number of poles	3
Terminals per Pole	1 line 4 load
Wire Size	Load 1, AWG 14...AWG 2, copper or aluminium Line 4, AWG 6...400 kcmil, copper or aluminium
Electrical Connection	Tin plated aluminium lugs
SCCR	100 kA UL 508 A
Ambient air temperature for operation	-40...302 °F (-40...150 °C)
Block Material	Phenolic block
Terminal Tightening Torque	Load lug 45 lbf.in (5.08 N.m) AWG 6...AWG 4 copper or aluminium Load lug 40 lbf.in (4.52 N.m) AWG 8 copper or aluminium Load lug 35 lbf.in (3.95 N.m) AWG 14 copper Line lug 275 lbf.in (31.07 N.m) AWG 6...350 kcmil copper or aluminium Load lug 50 lbf.in (5.65 N.m) AWG 2 copper or aluminium Load lug 35 lbf.in (3.95 N.m) AWG 12...AWG10 copper or aluminium
Wire stripping length	Line 1.06 in (26.92 mm) Load 0.56 in (14.22 mm) top Load 1 in (25.40 mm) bottom
Height	3.38 in (85.85 mm)

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Width	1.94 in (49.28 mm)
Depth	2.61 in (66.29 mm)
End Barrier	9080LB33
Net Weight	1.57 lb(US) (0.71 kg)

Environment

Certifications	CSA file 70361 class 6228 01 UL recognized E60616 CCN XCFR2 CE
----------------	--

Ordering and shipping details

Category	21711 - 9080 LB
Discount Schedule	CP1
GTIN	00785901157090
Nbr. of units in pkg.	1
Package weight(Lbs)	24.96 oz (707.604 g)
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	3.00 in (7.62 cm)
Package 1 width	4.30 in (10.922 cm)
Package 1 Length	5.20 in (13.208 cm)
Unit Type of Package 2	CAR
Number of Units in Package 2	16
Package 2 Weight	26.34 lb(US) (11.948 kg)
Package 2 Height	11.30 in (28.702 cm)
Package 2 width	9.50 in (24.13 cm)
Package 2 Length	13.40 in (34.036 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
RECh Regulation	RECh Declaration
RECh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)

Contractual warranty

Warranty	18 months
----------	-----------