# Product data sheet Characteristics

## **CD324N**

Safety switch, general duty, fusible, 200A, 120/240 VAC, 3 poles, 30 hp, solid neutral, NEMA 1

Product availability: Stock - Normally stocked in distribution facility

SQUARE D



Price\*: 2,019.00 USD



### Main

Product or component type	Single Throw Safety Switch
Series name	General duty

#### Complementary

1		
Line Rated Current	200 A	3
Device composition	Neutral (factory installed)	
Disconnector device type	Fusible disconnect	
Short-circuit current	100 kA maximum cartridge	
Device mounting	Surface	<u> </u>
Number of poles	3	
Electrical connection	Lugs	÷
[Ue] rated operational voltage	120/240 V AC	2 2. T
Maximum Horse Power Rating	7.5 hp 240 V at AC 50-60 Hz for 1 phase conforming to NEC 240.6 15 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 15 hp 240 V at AC 50-60 Hz for 1 phase conforming to NEC 430.52 30 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52	o di si
AWG gauge	AWG 6250 kcmil copper or aluminium	
Tightening torque	275 lbf.in (31.07 N.m) (AWG 6250 kcmil)	
Height	29 in (736.60 mm)	
Width	19 in (482.60 mm)	<u></u>
Depth	8.25 in (209.55 mm)	  

#### **Environment**

Product certifications	CSA	F

<sup>\*</sup> Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

NEMA degree of protection	NEMA 1 galvannealed steel
Ordering and chinning details	
Ordering and shipping details  Category	00154 - CD&CDU CANADA SW NON-NEGO
Discount Schedule	DE1A
GTIN	
	00785901391555
Nbr. of units in pkg.	1
Package weight(Lbs)	55.5 lb(US) (25.17 kg)
Returnability	Yes
Country of origin	US
Packing Units	
Package 1 Height	7.80 in (19.812 cm)
Package 1 width	19.80 in (50.292 cm)
Package 1 Length	30.50 in (77.470 cm)
Office Or other selection	
Offer Sustainability	
Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile

$\sim$		
Con	tractual	warrantv

PVC free

Contractual warranty	
Warranty	18 months

Yes