



Price\* : 1,452.00 USD



## Main

Range	Square D
Product	Single Throw Safety Switch
Current Rating	30 A
Enclosure Rating	NEMA 3R/12 galvanized steel
Horsepower Rating	5 hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 15 hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 7.5 hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 20 hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 5 hp 250 V at DC 15 hp 600 V at DC
Disconnect Type	Fusible disconnect
Short Circuit Current Rating	10 kA 200 kA
Mounting Type	Surface
Number of Poles	3
Phase	3 phase
Certifications	CSA
Voltage Rating	600 V AC/DC
Wire Configuration	4-wire
Wire Size	AWG 12...AWG 2 aluminium AWG 14...AWG 2 copper

## Complementary

Tightening torque	45 lbf.in (5.08 N.m) 0.02 in <sup>2</sup> (13.3 mm <sup>2</sup> ) (AWG 6) 40 lbf.in (4.52 N.m) 0.01 in <sup>2</sup> (8.367 mm <sup>2</sup> ) (AWG 8) 35 lbf.in (3.95 N.m) 0.00...0.01 in <sup>2</sup> (2.06...5.21 mm <sup>2</sup> ) (AWG 14...AWG 10)
Width	7.55 in (191.77 mm)
Height	14.6 in (370.84 mm)

\* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Depth	4.96 in (125.98 mm)
-------	---------------------

## Ordering and shipping details

Category	00153-C,CH&CHU CANADA SW NON-NEG
Discount Schedule	DE1
GTIN	00785901594550
Nbr. of units in pkg.	1
Package weight(Lbs)	12.00 lb(US) (5.443 kg)
Returnability	Yes
Country of origin	US


## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	31.44 in (79.849 cm)
Package 1 width	7.37 in (18.732 cm)
Package 1 Length	13.44 in (34.129 cm)




## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
PVC free	Yes

## Approximate Dimensions



Connections and Wiring Diagrams

WIRING DIAGRAMS		
FUSIBLE		NOT FUSIBLE
		
H221AWK	H321AWK H361AWK	HU361AWK HU361AWKEI