Product data sheet **Characteristics**

CH365AWK 400A 3P Type12 600VAC/DC Heavy Duty Fusible Safety Switch

Product availability : Stock - Normally stocked in distribution facility

SQUARE D



Price* : 5,462.00 USD



Main

Product	Single Throw Safety Switch	
Disconnect Type	Fusible disconnect	
Number of Poles	3	
Electrical Connection	Lugs	
Duty Rating	Heavy duty	

Complementary

-		
Main		
Product	Single Throw Safety Switch	
Disconnect Type	Fusible disconnect	
Number of Poles	3	
Electrical Connection	Lugs	
Duty Rating	Heavy duty	
Complementary		
Line Rated Current	400 A	
Factory Installed Neutral	None	
Mounting Type	Surface	
Voltage Rating	600 V AC/DC	
Maximum Horse Power Rating	100 hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 250 hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 125 hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 350 hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 50 hp 250 V at DC 50 hp 600 V at DC	
Wire Size	AWG 1/0750 kcmil copper or aluminium	
Tightening torque	550 lbf.in (62.14 N.m) (AWG 1/0750 kcmil)	
Height	46.25 in (1174.75 mm)	
Width	26.25 in (666.75 mm)	
Depth	10.13 in (257.30 mm)	
Environment		
Certifications	CSA	
Enclosure Rating	NEMA 3R/12 galvannealed steel	
* Price is "List Price" and may be subject to a trac	e discount – check with your local distributor or retailer for actual price.	

Environment

Certifications	CSA
Enclosure Rating	NEMA 3R/12 galvannealed steel

Ordering and shipping details

Category	00153 - C,CH&CHU CANADA SW NON-NEG
Discount Schedule	DE1
GTIN	00785901344667
Nbr. of units in pkg.	1
Package weight(Lbs)	159 lb(US) (72.12 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Package 1 Height	2.22 ft (0.678 m)	
Package 1 width	1.06 ft (0.323 m)	
Package 1 Length	4.27 ft (1.303 m)	

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	
Environmental Disclosure	Product Environmental Profile	
PVC free	Yes	
Halogen content performance	Halogen free plastic parts product	