

Product data sheet

Characteristics

D325NR

Safety switch, general duty, fusible, 400 A, 3 poles, 125 hp, 240 VAC, NEMA 3R, neutral factory installed

Product availability : Stock - Normally stocked in distribution facility



Price* : 3,893.00 USD



Main

Product	Single Throw Safety Switch
Duty Rating	General duty
Device application	Residential
Disconnect Type	Fusible disconnect switch
Factory Installed Neutral	Neutral (factory installed)
Phase	3 phase
Number of Poles	3
Current Rating	400 A
Voltage Rating	240 V AC
Enclosure Rating NEMA	NEMA 3R
Maximum Horse Power Rating	50 hp 240 V at AC 60 Hz for 3 phase conforming to NEC 240.6 125 hp 240 V at AC 60 Hz for 3 phase conforming to NEC 430.52

Complementary

Short Circuit Current Rating	100 kA maximum depending on fuse H, K, J or R
Fuse type	H, K, J or R
Mounting Type	Surface
Electrical Connection	Lugs
Wiring configuration	4-wire (3PH + G)
Wire Size	AWG 10...AWG 6 aluminium/copper
Tightening torque	340 lbf.in (38.41 N.m) (AWG 1/0...250 kcmil)
Depth	10.13 in (257.30 mm)
Width	22.25 in (565.15 mm)
Height	30.63 in (778.00 mm)

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Jul 30, 2021

Net Weight	99.21 lb(US) (45 kg)
------------	----------------------

Environment

Certifications	UL listed file E2875
----------------	----------------------

Ordering and shipping details

Category	00107 - D & DU SW,NEMA3R, 400-600A
Discount Schedule	DE1A
GTIN	00785901461579
Nbr. of units in pkg.	1
Package weight(Lbs)	69.98 lb(US) (31.742 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	11.00 in (27.94 cm)
Package 1 width	23.00 in (58.42 cm)
Package 1 Length	32.00 in (81.28 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

Contractual warranty

Warranty	18 months
----------	-----------

Approximate Dimensions

