Product data sheet Characteristics

D325NT

Safety switch, general duty, fusible, 400A, 3 poles, 50 hp, 240 VAC, NEMA 1, fuse class T, neutral factory installed

Product availability: Non-Stock - Not normally stocked in distribution facility





Price*: 4,491.00 USD



Main

| Product | Single Throw Safety Switch | |
|----------------------------|--|----------|
| Duty Rating | General duty | |
| Device application | Residential | <u>.</u> |
| Disconnect Type | Fusible disconnect switch | |
| Factory Installed Neutral | Neutral (factory installed) | |
| Phase | 3 phase | : |
| Number of Poles | 3 | |
| Current Rating | 400 A | <u> </u> |
| Voltage Rating | 240 V AC | ğ |
| Enclosure Rating NEMA | NEMA 1 | ā d |
| Maximum Horse Power Rating | n Horse Power Rating 50 hp 240 V at AC 60 Hz for 3 phase conforming to NEC 240.6 | |
| | | |

Complementary

| Short Circuit Current Rating | 100 kA T | | |
|------------------------------|--|--|--|
| Fuse type | Т | | |
| Mounting Type | Surface | | |
| Electrical Connection | Lugs | | |
| Wiring configuration | 4-wire (3PH + G) | | |
| Wire Size | AWG 1/0600 kcmil aluminium/copper 2 x AWG 1/02 x 300 kcmil aluminium/copper | | |
| Tightening torque | 340 lbf.in (38.41 N.m) (AWG 1/0750 kcmil) 340 lbf.in (38.41 N.m) (2 x AWG 1/02 x 300 kcmil) | | |
| Depth | 8.88 in (225.55 mm) | | |
| Width | 24.88 in (631.95 mm) | | |

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| Height | 45.12 in (1146.05 mm) |
|------------------------------|---|
| Net Weight | 108.03 lb(US) (49 kg) |
| Environment | |
| Certifications | UL listed file E2875 |
| Ordering and shipping detail | S S |
| Category | 00059 - MISC G/D SWITCHES |
| Discount Schedule | DE1A |
| GTIN | 00785901003649 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 1 lb(US) (0.45 kg) |
| Returnability | No |
| Country of origin | CA |
| Offer Sustainability | |
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACh Regulation | REACh Declaration |
| REACh free of SVHC | Yes |
| | |

| | more information go to www.P65Warnings.ca.gov | |
|-----------------------------|---|--|
| REACh Regulation | REACh Declaration | |
| REACh free of SVHC | Yes | |
| EU RoHS Directive | Compliant EU RoHS Declaration | |
| Mercury free | Yes | |
| RoHS exemption information | Yes | |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information. | |
| Environmental Disclosure | Product Environmental Profile | |
| PVC free | Yes | |
| Halogen content performance | Halogen free plastic parts product | |

| Contractual warranty | | | |
|----------------------|-----------|--|--|
| Warranty | 18 months | | |