# Product data sheet Characteristics

# **DU321RB**

Safety switch, general duty, non fusible, 30A, 3 poles, 7.5 hp, 240 VAC, NEMA 3R, bolt-on provision

Product availability: Stock - Normally stocked in distribution facility

SQUARE 1



Price\*: 293.00 USD



## Main

IVIAIII		9
Product	Single Throw Safety Switch	-
Duty Rating	General duty	
Device application	Residential	
Disconnect Type	Non-fusible disconnect switch	
Factory Installed Neutral	None	<u> </u>
Phase	3 phase	
Number of Poles	3	
Current Rating	30 A	
Voltage Rating	240 V AC	, ,
Enclosure Rating NEMA	NEMA 3R	
Maximum Horse Power Rating	3 hp 240 V at AC 60 Hz for 1 phase conforming to NEC 430.52 7.5 hp 240 V at AC 60 Hz for 3 phase conforming to NEC 430.52	, ,

### Complementary

Mounting Type	Surface	
Electrical Connection	Lugs	
Wiring configuration	3-wire	
Wire Size	AWG 14AWG 6 copper AWG 12AWG 6 aluminium	
Tightening torque	30 lbf.in (3.39 N.m) 0.000.02 in² (2.0813.3 mm²) (AWG 14AWG 6)	
Depth	3.75 in (95.25 mm)	
Width	7.75 in (196.85 mm)	
Height	9.63 in (244.60 mm)	
Net Weight	19.84 lb(US) (9 kg)	

<sup>\*</sup> Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

## Environment

0 (' (' ('	LII 15-15-1 CI- E007E	
Certifications	UL listed file E2875	
Ochanodaorio	OL HOLOG IIIO LEGITO	

## Ordering and shipping details

Category	00106 - D & DU SW,NEMA3R, 30-200A
Discount Schedule	DE1A
GTIN	00785901491620
Nbr. of units in pkg.	1
Package weight(Lbs)	4.43 lb(US) (2.01 kg)
Returnability	Yes
Country of origin	MX

### Packing Units

PCE
10.00 in (25.4 cm)
7.60 in (19.304 cm)
5.20 in (13.208 cm)
CAR
5
25.55 lb(US) (11.589 kg)
10.70 in (27.178 cm)
10.40 in (26.416 cm)
23.90 in (60.706 cm)
PAL
160
870.00 lb(US) (394.625 kg)
47.00 in (119.38 cm)
40.00 in (101.6 cm)
48.00 in (121.92 cm)


## Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)	
Environmental Disclosure	Product Environmental Profile	
PVC free	Yes	

### Contractual warranty


Warranty	18 months

#### **Dimensions**



TOP OF NEMA TYPE 3R DEVICES HAVE PROVISIONS FOR MAX 2.50/[64] BOLT-ON HUB.
ALL DIMENSIONS ARE APPROXIMATE. REFER TO TECHNICAL DRAWINGS AND DOCUMENTATION FOR COMPLETE DETAILS.

Wiring Diagram



DU321RB