Product data sheet **Characteristics** 

# H222AWK Safety switch, heavy duty, fusible, 60A, 2 poles, 15 hp, 240 VAC/250 VDC, NEMA 12

Product availability : Stock - Normally stocked in distribution facility

SQUARE D



Price\* : 647.00 USD



#### Main

a de la dela dela dela dela dela dela de		
Vain		
Product	Single Throw Safety Switch	
Duty Rating	Heavy duty	
Device application	Heavy application	
Disconnect Type	Fusible disconnect	
Factory Installed Neutral	None	
Phase	3 phase	
Number of Poles	2	
Current Rating	60 A	
Voltage Rating	250 V DC 240 V AC	
Enclosure Rating	NEMA 3R/12 galvannealed steel	
Maximum Horse Power Rating	3 hp 240 V at AC 50-60 Hz for 1 phase conforming to NEC 240.6 7.5 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 10 hp 240 V at AC 50-60 Hz for 1 phase conforming to NEC 430.52 15 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 10 hp 250 V at DC	
Complementary		
Short Circuit Current Rating	10 kA H or K 200 kA R, J or L	
Fuse type	H or K R, J or L	
Mounting Type	Surface	
Electrical Connection	Lugs	
Wiring configuration	2-wire	
Wire Size	AWG 14AWG 3 copper AWG 12AWG 3 aluminium	
* Price is "List Price" and may be subject to a trace	le discount – check with your local distributor or retailer for actual price.	
lul 20, 2021		

#### Complementary

Short Circuit Current Rating	10 kA H or K 200 kA R, J or L	
Fuse type	H or K R, J or L	
Mounting Type	Surface	
Electrical Connection	Lugs	
Wiring configuration	2-wire	
Wire Size	AWG 14AWG 3 copper AWG 12AWG 3 aluminium	



Tightening torque	50 lbf.in (5.65 N.m) (AWG 3)	
	45 lbf.in (5.08 N.m) (AWG 6AWG 4)	
	40 lbf.in (4.52 N.m) 0.01 in² (8.367 mm²) (AWG 8)	
	50 lbf.in (5.65 N.m) 0.000.01 in² (2.065.261 mm²) (AWG 14AWG 10)	
Depth	4.96 in (125.98 mm)	
Width	6.63 in (168.40 mm)	
Height	14.6 in (370.84 mm)	
Net Weight	11.02 lb(US) (5 kg)	

#### Environment

Cortifications	III listed file F2875
Certifications	UL listed file E2875

### Ordering and shipping details

Catagany	00113 - H&HU SW,2&3P,N12,30-200A
Category	00113 - HAND SW,2&3P,N12,30-200A
Discount Schedule	DE1
GTIN	00785901477822
Nbr. of units in pkg.	1
Package weight(Lbs)	10.02 lb(US) (4.545 kg)
Returnability	Yes
Country of origin	US

# Packing Units

Unit Type of Package 1	PCE
Package 1 Height	5.50 in (13.97 cm)
Package 1 width	7.70 in (19.558 cm)
Package 1 Length	17.50 in (44.45 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	
Environmental Disclosure	Product Environmental Profile	
PVC free	Yes	

### Contractual warranty

Warranty

18 months