Product data sheet Characteristics

H222N

Safety switch, heavy duty, fusible, 60A, 2 poles, 15 hp, 240 VAC/250 VDC, neutral factory installed, NEMA1

Product availability: Stock - Normally stocked in distribution facility





Price*: 471.00 USD



Main

| Single Throw Safety Switch | - |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | € |
| Heavy duty | |
| Heavy application | |
| Fusible disconnect | |
| Neutral (factory installed) | |
| 3 phase | |
| 2 | |
| 60 A | |
| 250 V DC 240 V AC | |
| NEMA 1 steel | |
| 3 hp 240 V at AC 50-60 Hz for 1 phase conforming to NEC 240.6 7.5 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 10 hp 240 V at AC 50-60 Hz for 1 phase conforming to NEC 430.52 15 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 10 hp 250 V at DC | sittute for and is not t |
| | Heavy application Fusible disconnect Neutral (factory installed) 3 phase 2 60 A 250 V DC 240 V AC NEMA 1 steel 3 hp 240 V at AC 50-60 Hz for 1 phase conforming to NEC 240.6 7.5 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 10 hp 240 V at AC 50-60 Hz for 1 phase conforming to NEC 430.52 15 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 |

Complementary

| Short Circuit Current Rating | 10 kA H or K | |
|------------------------------|--------------------|---|
| | 200 kA R, J or L | |
| Fuse type | H or K | |
| | R, J or L | |
| Mounting Type | Surface | |
| Electrical Connection | Lugs | |
| Wiring configuration | 3-wire | · |
| Wire Size | AWG 14AWG 3 copper | |

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| AWG | 12AWG | 3 aluminium | |
|-----|-------|-------------|--|
| | | | |

| Tightening torque | 50 lbf.in (5.65 N.m) (AWG 3) | |
|-------------------|------------------------------------------------------------------|--|
| | 45 lbf.in (5.08 N.m) (AWG 6AWG 4) | |
| | 40 lbf.in (4.52 N.m) 0.01 in² (8.367 mm²) (AWG 8) | |
| | 50 lbf.in (5.65 N.m) 0.000.01 in² (2.065.261 mm²) (AWG 14AWG 10) | |
| Depth | 4.88 in (123.95 mm) | |
| Width | 6.5 in (165.10 mm) | |
| Height | 14.6 in (370.84 mm) | |
| Net Weight | 8.82 lb(US) (4 kg) | |

Environment

|--|

Ordering and shipping details

| Category | 00008 - H&HU SW,2&3P,N1,30-200A |
|-----------------------|---------------------------------|
| Discount Schedule | DE1 |
| GTIN | 00785901477709 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 7.95 lb(US) (3.61 kg) |
| Returnability | Yes |
| Country of origin | US |

Packing Units

| Package 1 Height | 5.20 in (13.208 cm) |
|------------------|----------------------|
| Package 1 width | 7.80 in (19.812 cm) |
| Package 1 Length | 16.20 in (41.148 cm) |

Offer Sustainability

| Sustainable offer status | Green Premium product | |
|----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov | |
| REACh Regulation | REACh Declaration | |
| REACh free of SVHC | Yes | |
| EU RoHS Directive | Compliant EU RoHS Declaration | |
| Mercury free | Yes | |
| RoHS exemption information | Yes | |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information. | |
| Environmental Disclosure | Product Environmental Profile | |
| PVC free | Yes | |

Contractual warranty

| Warranty | 18 months |
|----------|-----------|