Product data sheet **Characteristics**

H224NA

Safety switch, heavy duty, fusible, 200A, 2 poles, 60 hp, 240 VAC/250 VDC, NEMA 12K, neutral factory installed

Product availability : Non-Stock - Not normally stocked in distribution facility

SQUARE 🖸



Price* : 2,087.00 USD



Main

<i>l</i> lain				
Product	Single Throw Safety Switch			
Duty Rating	Heavy duty			
Device application	Heavy application			
Disconnect Type	Fusible disconnect			
Factory Installed Neutral	Neutral (factory installed)			
Phase	3 phase			
Number of Poles	2			
Current Rating	200 A			
/oltage Rating	250 V DC 240 V AC			
Enclosure Rating	NEMA 12K			
Maximum Horse Power Rating	15 hp 240 V at AC 50-60 Hz for 1 phase conforming to NEC 240.6 25 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 60 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 40 hp 250 V at DC			
Complementary				
Mounting Type	Surface			
Viring configuration	3-wire			
Vire Size	AWG 6250 kcmil copper or aluminium			
Fightening torque	275 lbf.in (31.07 N.m) 0.020.20 in ² (13.3127 mm ²) (AWG 6250 kcmil)			
Depth	8.75 in (222.25 mm)			
Vidth	17.25 in (438.15 mm)			
Height	29 in (736.60 mm)			
Net Weight	53.99 lb(US) (24.49 kg)			
Price is "List Price" and may be subject to a trac	de discount – check with your local distributor or retailer for actual price.			

Complementary

Mounting Type	Surface		
Wiring configuration	3-wire		
Wire Size	AWG 6250 kcmil copper or aluminium		
Tightening torque	275 lbf.in (31.07 N.m) 0.020.20 in ² (13.3127 mm ²) (AWG 6250 kcmil)		
Depth	8.75 in (222.25 mm)		
Width	17.25 in (438.15 mm)		
Height	29 in (736.60 mm)		
Net Weight	53.99 lb(US) (24.49 kg)		

UL listed file E2875

Ordering and shipping details

Category	00114 - H&HU SW,2&3P,N12K,30-200A	
Discount Schedule	DE1	
GTIN	00785901478195	
Nbr. of units in pkg.	1	
Package weight(Lbs)	10 lb(US) (4.54 kg)	
Returnability	No	
Country of origin	US	

Packing Units

	DCE		
Unit Type of Package 1	PCE		

Offer Sustainability

Sustainable offer status	atus Green Premium product		
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. Fo more information go to www.P65Warnings.ca.gov		
REACh Regulation	REACh Declaration		
REACh free of SVHC	Yes		
EU RoHS Directive	Compliant EU RoHS Declaration		
Toxic heavy metal free	Yes		
Mercury free	Yes		
RoHS exemption information	Yes		
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)		
Environmental Disclosure	Product Environmental Profile		
PVC free	Yes		

Contractual warranty

Warranty

18 months