Product data sheet Characteristics

H226

Safety switch, heavy duty, fusible, 600A, 2 poles, 200 hp, 240 VAC/250 VDC, NEMA 1

Product availability: Non-Stock - Not normally stocked in distribution facility





Price*: 8,136.00 USD



Main

Mairi	
Product	Single Throw Safety Switch
Duty Rating	Heavy duty
Device application	Heavy application
Disconnect Type	Fusible disconnect
Factory Installed Neutral	None
Phase	3 phase
Number of Poles	2
Current Rating	600 A
Voltage Rating	250 V DC 240 V AC
Enclosure Rating	NEMA 1 steel
Maximum Horse Power Rating	75 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 200 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 50 hp 250 V at DC

Complementary

		·
Short Circuit Current Rating	10 kA H or K 200 kA R, J or L	
Fuse type	H or K R, J or L	
Mounting Type	Surface	į
Electrical Connection	Lugs	.9
Wiring configuration	2-wire	
Wire Size	AWG 3/0500 kcmil copper or aluminium	
Tightening torque	375 lbf.in (42.37 N.m) (AWG 3/0500 kcmil)	-
Depth	10.13 in (257.30 mm)	į.

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Width	27.63 in (701.80 mm)	
Height	50.25 in (1276.35 mm)	
Net Weight	175.05 lb(US) (79.4 kg)	

Environment

Certifications	UL listed file E2875

Ordering and shipping details

Category	00053 - H&HU SW,NEMA1,400-1200A
Discount Schedule	DE1
GTIN	00785901450399
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No
Country of origin	US

Offer Sustainability

Green Premium product
WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Declaration
Yes
Compliant EU RoHS Declaration
Yes
Yes
China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Product Environmental Profile
Yes
Halogen free plastic parts product

Contractual warranty

on a distance of the second of	
Warranty	18 months