Product data sheet Characteristics

H227AWK

Safety switch, heavy duty, fusible, 800A, 2 poles, 50 hp, 240 VAC/250 VDC, NEMA 12

Product availability: Non-Stock - Not normally stocked in distribution facility





Price*: 10,325.00 USD



Main

Product	Single Throw Safety Switch	
Duty Rating	Heavy duty	9 9
Device application	Heavy application	# 5
Disconnect Type	Fusible disconnect	: <u>:</u> .c. .g.
Factory Installed Neutral	None	<u> </u>
Phase	3 phase	<u>}</u>
Number of Poles	2	
Current Rating	800 A	
Voltage Rating	250 V DC 240 V AC	n datem
Enclosure Rating	NEMA 3R/12 galvannealed steel	<u> </u>
Maximum Horse Power Rating	50 hp 240 V at AC 50-60 Hz for 1 phase conforming to NEC 240.6 50 hp 250 V at DC	

Complementary

Short Circuit Current Rating	200 kA maximum L
Fuse type	L
Mounting Type	Surface
Electrical Connection	Lugs
Wiring configuration	2-wire
Wire Size	AWG 3/0750 kcmil copper or aluminium
Tightening torque	375 lbf.in (42.37 N.m) 0.130.59 in² (85.01380 mm²) (AWG 3/0750 kcmil)
Depth	17.75 in (450.85 mm)
Width	36.62 in (930.15 mm)
Height	69.13 in (1755.90 mm)

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



Net Weight	360.90 lb(US) (163.7 kg)
Environment	
Certifications	UL listed file E2875
Ordering and shipping details	
Category	00155 - H&HU SW,NEMA12,400-1200A
Discount Schedule	DE1
GTIN	00785901298847
Nbr. of units in pkg.	1
Package weight(Lbs)	366 lb(US) (166.01 kg)
Returnability	No
Country of origin	MX

~ ~ ~ ~	\sim			
Offer	CITIC!	taina	nı	lit\/
Ollei	ous	іаніа	UI.	IILV

Green Premium product	
WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Declaration	
Compliant EU RoHS Declaration	
Yes	
Yes	
China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	
Product Environmental Profile	
Yes	
Halogen free plastic parts product	

Contractual warranty

Contraction warranty		
Warranty	18 months	