Product data sheet Characteristics

H321NDS

Safety switch, heavy duty, fusible, 30A, 3 poles, 7.5 hp, 240 VAC/250 VDC, NEMA 4, 4X, 5, 304 steel, neutral





Price*: 2,282.00 USD



Main

IVIAIII		7
Product	Single Throw Safety Switch	
Duty Rating	Heavy duty	- 5
Device application	Heavy application) ::::::::::::::::::::::::::::::::::::
Disconnect Type	Fusible disconnect	<u> </u>
Factory Installed Neutral	Neutral (factory installed)	
Phase	3 phase	
Number of Poles	3	
Current Rating	30 A	
Voltage Rating	250 V DC 240 V AC	
Enclosure Rating	NEMA 4/4X/5 stainless steel 304	- 0
Maximum Horse Power Rating	1.5 hp 240 V at AC 50-60 Hz for 1 phase conforming to NEC 240.6 3 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 3 hp 240 V at AC 50-60 Hz for 1 phase conforming to NEC 430.52 7.5 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 5 hp 250 V at DC	of or and is not to

Complementary

Complementary		
Short Circuit Current Rating	10 kA H or K 200 kA R, J or L	
Fuse type	H or K R, J or L	
Mounting Type	Surface	
Electrical Connection	Lugs	
Wiring configuration	4-wire (3PH + G)	
Wire Size	AWG 12AWG 6 aluminium AWG 14AWG 6 copper	

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Tightening torque	45 lbf.in (5.08 N.m) 0.02 in² (13.3 mm²) (AWG 6) 40 lbf.in (4.52 N.m) 0.01 in² (8.367 mm²) (AWG 8) 35 lbf.in (3.95 N.m) 0.000.01 in² (2.065.261 mm²) (AWG 14AWG 10)	
Depth	5.11 in (129.79 mm)	
Width	7.22 in (183.39 mm)	
Height	14.93 in (379.22 mm)	
Net Weight	13.23 lb(US) (6 kg)	

Environment

Certifications	UL listed file E2875
00.10400	02 110104 1110 22010

Ordering and shipping details

00010-H&HU SW,2&3P,N4,SS,30-200A
DE1
00785901694113
1
12.50 lb(US) (5.67 kg)
Yes
US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	5.70 in (14.478 cm)
Package 1 width	9.10 in (23.114 cm)
Package 1 Length	17.30 in (43.942 cm)

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	
Environmental Disclosure	Product Environmental Profile	
PVC free	Yes	

Contractual warranty

Warranty	18 months

Approximate Dimensions

