Product data sheet Characteristics

H326N

Safety switch, heavy duty, fusible, 600A, 3 poles, 200 hp, 240 VAC/250 VDC, neutral factory installed, NEMA1

Product availability: Stock - Normally stocked in distribution facility

SQUARE D



Price*: 6,519.00 USD



Main

IVIAIII		9
Product	Single Throw Safety Switch	
Duty Rating	Heavy duty	
Device application	Heavy application	
Disconnect Type	Fusible disconnect	
Factory Installed Neutral	Neutral (factory installed)	
Phase	3 phase	: <u>:</u> 7
Number of Poles	3	
Current Rating	600 A	
Voltage Rating	250 V DC 240 V AC	pasi for
Enclosure Rating	NEMA 1 steel	
Maximum Horse Power Rating	75 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 200 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 50 hp 250 V at DC	r and is not t

Complementary

Complementary		
Short Circuit Current Rating	10 kA H or K 200 kA R, J or L	
Fuse type	H or K R, J or L	
Mounting Type	Surface	
Electrical Connection	Lugs	
Wiring configuration	4-wire (3PH + G)	
Wire Size	AWG 3/0500 kcmil copper or aluminium	
Tightening torque	375 lbf.in (42.37 N.m) (AWG 3/0500 kcmil)	

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Depth	10.13 in (257.30 mm)
Width	27.63 in (701.80 mm)
Height	50.25 in (1276.35 mm)
Net Weight	179.90 lb(US) (81.6 kg)

Environment

Certifications UL listed file E2875	
-------------------------------------	--

Ordering and shipping details

Category	00053 - H&HU SW,NEMA1,400-1200A		
Discount Schedule	DE1		
GTIN	00785901451686		
Nbr. of units in pkg.	1		
Package weight(Lbs)	175 lb(US) (79.38 kg)		
Returnability	Yes		
Country of origin	MX		

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	1.17 ft (0.356 m)	
Package 1 width	2.33 ft (0.711 m)	
Package 1 Length	4.33 ft (1.321 m)	

Offer Sustainability

Sustainable offer status	Green Premium product		
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov		
REACh Regulation	REACh Declaration		
REACh free of SVHC	Yes		
EU RoHS Directive	Compliant EU RoHS Declaration		
Mercury free	Yes		
RoHS exemption information	Yes		
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.		
Environmental Disclosure	Product Environmental Profile		
PVC free	Yes		
Halogen content performance	Halogen free plastic parts product		

Contractual warranty

Warranty	18 months	