

# H328AWK

Safety switch, heavy duty, fusible, 1200A, 3 poles,  
250 hp, 240 VAC/250 VDC, NEMA 12

Product availability : Non-Stock - Not normally stocked in distribution facility



Price\* : 17,450.00 USD



## Main

|                            |                                                                                                                                                                                                                            |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product                    | Single Throw Safety Switch                                                                                                                                                                                                 |
| Duty Rating                | Heavy duty                                                                                                                                                                                                                 |
| Device application         | Heavy application                                                                                                                                                                                                          |
| Disconnect Type            | Fusible disconnect                                                                                                                                                                                                         |
| Factory Installed Neutral  | None                                                                                                                                                                                                                       |
| Phase                      | 3 phase                                                                                                                                                                                                                    |
| Number of Poles            | 3                                                                                                                                                                                                                          |
| Current Rating             | 1200 A                                                                                                                                                                                                                     |
| Voltage Rating             | 250 V DC<br>240 V AC                                                                                                                                                                                                       |
| Enclosure Rating           | NEMA 3R/12 galvanized steel                                                                                                                                                                                                |
| Maximum Horse Power Rating | 50 hp 240 V at AC 50-60 Hz for 1 phase conforming to NEC 240.6<br>100 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6<br>250 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52<br>50 hp 250 V at DC |

## Complementary

|                              |                                                                                                         |
|------------------------------|---------------------------------------------------------------------------------------------------------|
| Short Circuit Current Rating | 200 kA maximum L                                                                                        |
| Fuse type                    | L                                                                                                       |
| Mounting Type                | Surface                                                                                                 |
| Electrical Connection        | Lugs                                                                                                    |
| Wiring configuration         | 3-wire (3P)                                                                                             |
| Wire Size                    | AWG 3/0...750 kcmil copper or aluminium                                                                 |
| Tightening torque            | 375 lbf.in (42.37 N.m) 0.13...0.59 in <sup>2</sup> (85.01...380 mm <sup>2</sup> ) (AWG 3/0...750 kcmil) |
| Depth                        | 17.75 in (450.85 mm)                                                                                    |
| Width                        | 36.62 in (930.15 mm)                                                                                    |

\* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

|            |                          |
|------------|--------------------------|
| Height     | 69.13 in (1755.90 mm)    |
| Net Weight | 369.05 lb(US) (167.4 kg) |

## Environment

|                |                      |
|----------------|----------------------|
| Certifications | UL listed file E2875 |
|----------------|----------------------|

## Ordering and shipping details

|                       |                                  |
|-----------------------|----------------------------------|
| Category              | 00155 - H&HU SW,NEMA12,400-1200A |
| Discount Schedule     | DE1                              |
| GTIN                  | 00785901436065                   |
| Nbr. of units in pkg. | 1                                |
| Package weight(Lbs)   | 362 lb(US) (164.20 kg)           |
| Returnability         | No                               |
| Country of origin     | MX                               |

## Offer Sustainability

|                             |                                                                                                                                                                                                                                                                                             |
|-----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status    | Green Premium product                                                                                                                                                                                                                                                                       |
| California proposition 65   | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation            | <a href="#">REACH Declaration</a>                                                                                                                                                                                                                                                           |
| EU RoHS Directive           | Compliant<br><a href="#">EU RoHS Declaration</a>                                                                                                                                                                                                                                            |
| Mercury free                | Yes                                                                                                                                                                                                                                                                                         |
| RoHS exemption information  | <a href="#">Yes</a>                                                                                                                                                                                                                                                                         |
| China RoHS Regulation       | <a href="#">China RoHS declaration</a><br>Product out of China RoHS scope. Substance declaration for your information.                                                                                                                                                                      |
| Environmental Disclosure    | <a href="#">Product Environmental Profile</a>                                                                                                                                                                                                                                               |
| PVC free                    | Yes                                                                                                                                                                                                                                                                                         |
| Halogen content performance | Halogen free plastic parts product                                                                                                                                                                                                                                                          |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|