# Product data sheet Characteristics

# H328NAWK

Safety switch, heavy duty, fusible, 1200A, 3 poles, 250 hp, 240 VAC/250 VDC, NEMA 12, neutral factory installed

Product availability: Non-Stock - Not normally stocked in distribution facility





Price\*: 20,015.00 USD



### Main

IVIAIII		9
Product	Single Throw Safety Switch	
Duty Rating	Heavy duty	<u>ر</u> و
Device application	Heavy application	<u> </u>
Disconnect Type	Fusible disconnect	
Factory Installed Neutral	Neutral (factory installed)	
Phase	3 phase	
Number of Poles	3	
Current Rating	1200 A	
Voltage Rating	250 V DC 240 V AC	- Ised for
Enclosure Rating	NEMA 3R/12 galvannealed steel	
Maximum Horse Power Rating	50 hp 240 V at AC 50-60 Hz for 1 phase conforming to NEC 240.6 100 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 250 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 50 hp 250 V at DC	e for and is not t

#### Complementary

Short Circuit Current Rating	200 kA maximum L	
Fuse type	L	
Mounting Type	Surface	
Electrical Connection	Lugs	
Wiring configuration	4-wire (3PH + G)	
Wire Size	AWG 3/0750 kcmil copper or aluminium	
Tightening torque	375 lbf.in (42.37 N.m) 0.130.59 in² (85.01380 mm²) (AWG 3/0750 kcmil)	
Depth	17.75 in (450.85 mm)	

<sup>\*</sup> Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Width	36.62 in (930.15 mm)	
Height	69.13 in (1755.90 mm)	
Net Weight	382.06 lb(US) (173.3 kg)	

# Environment

Certifications	UL listed file E2875
----------------	----------------------

# Ordering and shipping details

Category	00155 - H&HU SW,NEMA12,400-1200A
Discount Schedule	DE1
GTIN	00785901046448
Nbr. of units in pkg.	1
Package weight(Lbs)	370 lb(US) (167.83 kg)
Returnability	No
Country of origin	MX

#### Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	
Environmental Disclosure	Product Environmental Profile	
PVC free	Yes	
Halogen content performance	Halogen free plastic parts product	

#### Contractual warranty

Warranty	18 months