

# Product data sheet

## Characteristics

# H361AWAVW

Safety switch, heavy duty, fusible, 30A, 600 VAC/ VDC, 3 poles, 20 hp, NEMA 12K, appleton, view window

Product availability : Non-Stock - Not normally stocked in distribution facility



Price\* : 3,490.50 USD



### Main

Product	Receptacle Switch
For Use With	Plug ACP3034BC Appleton Powertite
Disconnect Type	Fusible disconnect switch
Phase	3 phase
Number of Poles	3
Current rating	30 A
Voltage Rating	600 V AC 250 V DC
Enclosure Rating NEMA 3R	NEMA 12K
Maximum Horse Power Rating	5 hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 15 hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 7.5 hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 20 hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 5 hp 250 V at DC conforming to NEC 240.6

### Complementary

Short-circuit Current Rating	10 kA H or K 200 kA R or J
Fuse Type	H or K R or J
Mounting Type	Surface
Electrical Connection	Receptacle
Wire Configuration	Without neutral 4-wire
Wire Size	AWG 12...AWG 2 aluminium AWG 14...AWG 2 copper

\* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Tightening torque	45 lbf.in (5.08 N.m) (AWG 6) 40 lbf.in (4.52 N.m) (AWG 8) 35 lbf.in (3.95 N.m) (AWG 14...AWG 10)
Depth	7 in (177.80 mm)
Width	10.5 in (266.70 mm)
Height	16.5 in (419.10 mm)
Net Weight	28.66 lb(US) (13 kg)

## Environment

Certifications	UL Listed
----------------	-----------

## Ordering and shipping details

Category	00124 - H&HU SW,W/APPLETON RECPT - WA
Discount Schedule	DE1
GTIN	00785901351917
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	Yes
Country of origin	US

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
RECh Regulation	<a href="#">RECh Declaration</a>
RECh free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------