Product data sheet Characteristics

H363AWA

Safety switch, heavy duty, fusible, 100A, 600 VAC/VDC, 3 poles, 75 hp, NEMA 12K, appleton powertite receptacle

Product availability: Non-Stock - Not normally stocked in distribution facility

SQUARE D



Price*: 3,758.00 USD



Main

Man			
Product	Receptacle Switch		
For Use With	Plug ACP1034CD Appleton Powertite		
Disconnect Type	Fusible disconnect switch		
Phase	3 phase		
Number of Poles	3		
Current rating	100 A		
Voltage Rating	600 V AC 250 V DC		
Enclosure Rating NEMA 3R	NEMA 12K		
Maximum Horse Power Rating	25 hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 60 hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 30 hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 75 hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 20 hp 250 V at DC conforming to NEC 240.6		

Complementary

- Compromising			
Mounting Type	Surface		
Electrical Connection	Receptacle		
Wire Configuration	4-wire		
Wire Size	AWG 12AWG 1/0 aluminium AWG 14AWG 1/0 copper		
Tightening torque	50 lbf.in (5.65 N.m) (AWG 3AWG 1) 45 lbf.in (5.08 N.m) (AWG 6AWG 4) 40 lbf.in (4.52 N.m) (AWG 8) 35 lbf.in (3.95 N.m) (AWG 14AWG 10)		
Depth	7 in (177.80 mm)		

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Width	10.5 in (266.70 mm)			
Height	20.5 in (520.70 mm)			
Net Weight	33.07 lb(US) (15 kg)			
Environment				
Certifications	UL Listed			
Ordering and shipping details				
Category	00124 - H&HU SW,W/APPLETON RECPT - WA			
Discount Schedule	DE1			
GTIN	00785901776277			
Nbr. of units in pkg.	1			
Package weight(Lbs)	20.00 lb(US) (9.072 kg)			
Returnability	No			
Country of origin	US			
Packing Units Unit Type of Package 1	PCE			
Package 1 Height	22.50 in (57.15 cm)			
Package 1 width	7.00 in (17.78 cm)			
Package 1 Length	10.37 in (26.352 cm)			
Offer Sustainability				
Sustainable offer status	Green Premium product			
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov			
REACh Regulation	REACh Declaration			
REACh free of SVHC	Yes			
EU RoHS Directive	Compliant EU RoHS Declaration			
Mercury free	Yes			
RoHS exemption information	Yes			
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.			
Environmental Disclosure	Product Environmental Profile			

Contractual warranty

PVC free

Contractadi Warranty			
Warranty	18 months		

Yes