

## Product data sheet

### Characteristics

# H363DSWA

Safety switch, heavy duty, fusible, 100A, 600 VAC/VDC, 3 poles, 75 hp, NEMA Type 4, 4X, 5, 304 steel, appleton

Product availability : Non-Stock - Not normally stocked in distribution facility



Price\* : 8,468.00 USD



### Main

|                            |                                                                                                                                                                                                                                                                                                                     |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product                    | Receptacle Switch                                                                                                                                                                                                                                                                                                   |
| For Use With               | Plug ACP1034CD Appleton Powertite                                                                                                                                                                                                                                                                                   |
| Disconnect Type            | Fusible disconnect switch                                                                                                                                                                                                                                                                                           |
| Phase                      | 3 phase                                                                                                                                                                                                                                                                                                             |
| Number of Poles            | 3                                                                                                                                                                                                                                                                                                                   |
| Current rating             | 100 A                                                                                                                                                                                                                                                                                                               |
| Voltage Rating             | 600 V AC<br>250 V DC                                                                                                                                                                                                                                                                                                |
| Enclosure Rating NEMA 3R   | NEMA 4/4X/5 stainless steel 304                                                                                                                                                                                                                                                                                     |
| Maximum Horse Power Rating | 25 hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6<br>60 hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52<br>30 hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6<br>75 hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52<br>20 hp 250 V at DC conforming to NEC 240.6 |

### Complementary

|                       |                                                                                                                                                        |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Mounting Type         | Surface                                                                                                                                                |
| Electrical Connection | Receptacle                                                                                                                                             |
| Wire Configuration    | 4-wire                                                                                                                                                 |
| Wire Size             | AWG 12...AWG 1/0 aluminium<br>AWG 14...AWG 1/0 copper                                                                                                  |
| Tightening torque     | 50 lbf.in (5.65 N.m) (AWG 3...AWG 1)<br>45 lbf.in (5.08 N.m) (AWG 6...AWG 4)<br>40 lbf.in (4.52 N.m) (AWG 8)<br>35 lbf.in (3.95 N.m) (AWG 14...AWG 10) |
| Depth                 | 6.97 in (177.04 mm)                                                                                                                                    |

\* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Jul 30, 2021

|        |                      |
|--------|----------------------|
| Width  | 11.25 in (285.75 mm) |
| Height | 28.00 in (711.20 mm) |

## Environment

|                |           |
|----------------|-----------|
| Certifications | UL Listed |
|----------------|-----------|

## Ordering and shipping details

|                       |                                       |
|-----------------------|---------------------------------------|
| Category              | 00124 - H&HU SW,W/APPLETON RECPT - WA |
| Discount Schedule     | DE1                                   |
| GTIN                  | 00785901878285                        |
| Nbr. of units in pkg. | 1                                     |
| Package weight(Lbs)   | 20.00 lb(US) (9.072 kg)               |
| Returnability         | Yes                                   |
| Country of origin     | US                                    |

## Packing Units

|                        |                    |
|------------------------|--------------------|
| Unit Type of Package 1 | PCE                |
| Package 1 Height       | 27.99 in (71.1 cm) |
| Package 1 width        | 11.26 in (28.6 cm) |
| Package 1 Length       | 6.97 in (17.7 cm)  |

## Offer Sustainability

|                            |                                                                                                                                                                                                                                                                                             |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                                                                                                                                                                                       |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                                                                                                                                                                                                           |
| REACH free of SVHC         | Yes                                                                                                                                                                                                                                                                                         |
| EU RoHS Directive          | Compliant<br><a href="#">EU RoHS Declaration</a>                                                                                                                                                                                                                                            |
| Mercury free               | Yes                                                                                                                                                                                                                                                                                         |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                                                                                                                                                                                         |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Product out of China RoHS scope. Substance declaration for your information.                                                                                                                                                                      |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                                                                                                                                                                                               |
| PVC free                   | Yes                                                                                                                                                                                                                                                                                         |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|