Product data sheet Characteristics

H367AWKVW

Safety switch, heavy duty, fusible, 800A, 3 poles, 500 hp, 600 VAC/DC, NEMA 12, viewing window

Product availability: Non-Stock - Not normally stocked in distribution facility





Price*: 18,648.00 USD



Main

Single Throw Safety Switch	
Heavy duty	
Heavy application	
Fusible disconnect	
None	
3 phase	
3	
800 A	
600 V AC/DC	
NEMA 3R/12	
200 hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 500 hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 250 hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 500 hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 50 hp 600 V at DC	

Complementary

Mounting Type	Surface	
Wiring configuration	3-wire	
Wire Size	AWG 3/0750 kcmil copper or aluminium	
Tightening torque	375 lbf.in (42.37 N.m) 0.130.59 in² (85.01380 mm²) (AWG 3/0750 kcmil)	
Depth	17.75 in (450.85 mm)	
Width	36.62 in (930.15 mm)	
Height	69.13 in (1755.90 mm)	

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Environment

0 115 11	
Certifications	III lietad tila E2875
Octilications	OL listed file L2075

Ordering and shipping details

00155 - H&HU SW,NEMA12,400-1200A	
DE1	
00785901657712	
1	
373.00 lb(US) (169.19 kg)	
No	
MX	

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	69.13 in (175.6 cm)
Package 1 width	36.61 in (93 cm)
Package 1 Length	17.76 in (45.1 cm)

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	
Environmental Disclosure	Product Environmental Profile	
PVC free	Yes	
Halogen content performance	Halogen free plastic parts product	

Contractual warranty

Marranti	10 manths	
Vvarranty	18 months	
•		