# Product data sheet Characteristics

# H368AWK

Safety switch, heavy duty, fusible, 1200A, 3 poles, 500 hp, 600 VAC/DC, NEMA 12

Product availability: Non-Stock - Not normally stocked in distribution facility





Price\*: 19,706.00 USD



#### Main

IVIAIII			
Product	Single Throw Safety Switch		
Duty Rating	Heavy duty		
Device application	Heavy application		
Disconnect Type	Fusible disconnect		
Factory Installed Neutral	None		
Phase	3 phase		
Number of Poles	3		
Current Rating	1200 A		
Voltage Rating	600 V AC/DC		
Enclosure Rating	NEMA 3R/12 galvannealed steel		
Maximum Horse Power Rating	200 hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 500 hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 250 hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 500 hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 50 hp 600 V at DC		

#### Complementary

o o mpromornary				
Short Circuit Current Rating	200 kA maximum L			
Fuse type	L			
Mounting Type	Surface			
Electrical Connection	Lugs			
Wiring configuration	3-wire			
Wire Size	AWG 3/0750 kcmil copper or aluminium			
Tightening torque	375 lbf.in (42.37 N.m) 0.130.59 in² (85.01380 mm²) (AWG 3/0750 kcmil)			
Depth	17.75 in (450.85 mm)			
Width	36.62 in (930.15 mm)			

<sup>\*</sup> Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Height	69.13 in (1755.90 mm)
Net Weight	373.02 lb(US) (169.2 kg)

#### Environment

Certifications	UL listed file E2875

### Ordering and shipping details

Category	00155 - H&HU SW,NEMA12,400-1200A		
Discount Schedule	DE1		
GTIN	00785901172918		
Nbr. of units in pkg.	1		
Package weight(Lbs)	370 lb(US) (167.83 kg)		
Returnability	No		
Country of origin	MX		

## Offer Sustainability

Sustainable offer status	Green Premium product		
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov		
REACh Regulation	REACh Declaration		
EU RoHS Directive	Compliant EU RoHS Declaration		
Mercury free	Yes		
RoHS exemption information	Yes		
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.		
Environmental Disclosure	Product Environmental Profile		
PVC free	Yes		
Halogen content performance	Halogen free plastic parts product		

#### Contractual warranty

Warranty	18 months	