Product data sheet Characteristics

H462DS


Safety switch, heavy duty, fusible, 60A, 4 poles, 50 hp, 600 VAC/DC, NEMA 4, 4X, 5, 304 steel

Product availability: Non-Stock - Not normally stocked in distribution facility





Price*: 4,603.50 USD



Main

Single Throw Safety Switch
Heavy duty
Heavy application
Fusible disconnect
None
3 phase
4
60 A
600 V AC/DC
NEMA 4/4X/5 stainless steel 304
15 hp 480 V at AC 50-60 Hz for 2 phases conforming to NEC 240.6 40 hp 480 V at AC 50-60 Hz for 2 phases conforming to NEC 430.52 20 hp 600 V at AC 50-60 Hz for 2 phases conforming to NEC 240.6 50 hp 600 V at AC 50-60 Hz for 2 phases conforming to NEC 430.52 10 hp 250 V at DC 30 hp 600 V at DC

Complementary

Short Circuit Current Rating	10 kA H or K 200 kA R, J or L	
Fuse type	H or K R, J or L	
Mounting Type	Surface	
Electrical Connection	Lugs	
Wiring configuration	4-wire	
Wire Size	AWG 14AWG 3 copper AWG 12AWG 3 aluminium	

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Tightening torque	50 lbf.in (5.65 N.m) (AWG 3) 45 lbf.in (5.08 N.m) (AWG 6AWG 4)	
	40 lbf.in (4.52 N.m) 0.01 in ² (8.367 mm ²) (AWG 8) 50 lbf.in (5.65 N.m) 0.000.01 in ² (2.065.261 mm ²) (AWG 14AWG 10)	
Depth	6.97 in (177.04 mm)	
Width	16.85 in (427.99 mm)	
Height	20.82 in (528.83 mm)	
Net Weight	33.07 lb(US) (15 kg)	

Environment

Certifications UL listed file E2875	
-------------------------------------	--

Ordering and shipping details

Category	00115 - H&HU SW,4&6P,N4,SS 30-200A
Discount Schedule	DE1
GTIN	00785901025931
Nbr. of units in pkg.	1
Package weight(Lbs)	10.00 lb(US) (4.536 kg)
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	25.70 in (65.268 cm)	
Package 1 width	16.80 in (42.672 cm)	
Package 1 Length	7.10 in (18.034 cm)	

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

Contractual warranty

Warranty	18 months