# Product data sheet Characteristics

# H464AWK

Safety switch, heavy duty, fusible, 200A, 4 poles, 150 hp, 600 VAC/DC, NEMA 12

Product availability: Stock - Normally stocked in distribution facility





Price\*: 3,222.00 USD



#### Main

Single Throw Safety Switch
Heavy duty
Heavy application
Fusible disconnect
None
3 phase
4
200 A
600 V AC/DC
NEMA 3R/12 galvannealed steel
50 hp 480 V at AC 50-60 Hz for 2 phases conforming to NEC 240.6 125 hp 480 V at AC 50-60 Hz for 2 phases conforming to NEC 430.52 60 hp 600 V at AC 50-60 Hz for 2 phases conforming to NEC 240.6 150 hp 600 V at AC 50-60 Hz for 2 phases conforming to NEC 430.52 40 hp 250 V at DC 50 hp 600 V at DC

#### Complementary

Complementary		
Short Circuit Current Rating	10 kA H or K 200 kA R, J or L	
Fuse type	H or K R, J or L	
Mounting Type	Surface	
Electrical Connection	Lugs	
Wiring configuration	4-wire	
Wire Size	AWG 6250 kcmil copper or aluminium	
Tightening torque	275 lbf.in (31.07 N.m) 0.020.20 in² (13.3127 mm²) (AWG 6250 kcmil)	

<sup>\*</sup> Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Depth	8.75 in (222.25 mm)
Width	18.63 in (473.20 mm)
Height	29 in (736.60 mm)
Net Weight	86.51 lb(US) (39.24 kg)

#### Environment

Certifications	UL listed file E2875
----------------	----------------------

#### Ordering and shipping details

<u> </u>	
Category	00116 - H&HU SW,4&6P,N12,30-200A
Discount Schedule	DE1
GTIN	00785901482604
Nbr. of units in pkg.	1
Package weight(Lbs)	76.00 lb(US) (34.473 kg)
Returnability	Yes
Country of origin	US

### Packing Units

Unit Type of Package 1	PCE
Package 1 Height	10.50 in (26.67 cm)
Package 1 width	26.00 in (66.04 cm)
Package 1 Length	31.80 in (80.772 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

#### Contractual warranty

Warranty	18 months	