

Product data sheet

Characteristics

H464DS

Safety switch, heavy duty, fusible, 200A, 4 poles,
150 hp, 600 VAC/DC, NEMA 4, 4X, 5, 304 steel

Product availability : Non-Stock - Not normally stocked in distribution facility



Price* : 12,596.00 USD



Main

| | |
|----------------------------|--|
| Product | Single Throw Safety Switch |
| Duty Rating | Heavy duty |
| Device application | Heavy application |
| Disconnect Type | Fusible disconnect |
| Factory Installed Neutral | None |
| Phase | 3 phase |
| Number of Poles | 4 |
| Current Rating | 200 A |
| Voltage Rating | 600 V AC/DC |
| Enclosure Rating | NEMA 4/4X/5 stainless steel 304 |
| Maximum Horse Power Rating | 50 hp 480 V at AC 50-60 Hz for 2 phases conforming to NEC 240.6 125 hp 480 V at AC 50-60 Hz for 2 phases conforming to NEC 430.52 60 hp 600 V at AC 50-60 Hz for 2 phases conforming to NEC 240.6 150 hp 600 V at AC 50-60 Hz for 2 phases conforming to NEC 430.52 40 hp 250 V at DC 50 hp 600 V at DC |

Complementary

| | |
|------------------------------|--|
| Short Circuit Current Rating | 10 kA H or K 200 kA R, J or L |
| Fuse type | H or K R, J or L |
| Mounting Type | Surface |
| Electrical Connection | Lugs |
| Wiring configuration | 4-wire |
| Wire Size | AWG 6...250 kcmil copper or aluminium |
| Tightening torque | 275 lbf.in (31.07 N.m) 0.02...0.20 in ² (13.3...127 mm ²) (AWG 6...250 kcmil) |

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Jul 30, 2021

| | |
|------------|-------------------------|
| Depth | 8.88 in (225.55 mm) |
| Width | 19.25 in (488.95 mm) |
| Height | 29 in (736.60 mm) |
| Net Weight | 73.50 lb(US) (33.34 kg) |

Environment

| | |
|----------------|----------------------|
| Certifications | UL listed file E2875 |
|----------------|----------------------|

Ordering and shipping details

| | |
|-----------------------|----------------------|
| Category | 00160 - DE1 MISC |
| Discount Schedule | DE1 |
| GTIN | 00785901369578 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 47 lb(US) (21.32 kg) |
| Returnability | No |
| Country of origin | US |

Packing Units

| | |
|------------------------|-----|
| Unit Type of Package 1 | PCE |
|------------------------|-----|

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure | Product Environmental Profile |
| PVC free | Yes |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|