Product data sheet Characteristics

H466

Safety switch, heavy duty, fusible, 600A, 4 poles, 500 hp, 600 VAC/DC, NEMA 1

Product availability: Non-Stock - Not normally stocked in distribution facility





Price*: 10,104.00 USD



Main

| Single Throw Safety Switch | |
|---|--|
| Heavy duty | |
| Heavy application | |
| Fusible disconnect | |
| None | |
| 3 phase | |
| 4 | |
| 600 A | |
| 600 V AC/DC | |
| NEMA 1 steel | |
| 150 hp 480 V at AC 50-60 Hz for 2 phases conforming to NEC 240.6 400 hp 480 V at AC 50-60 Hz for 2 phases conforming to NEC 430.52 200 hp 600 V at AC 50-60 Hz for 2 phases conforming to NEC 240.6 500 hp 600 V at AC 50-60 Hz for 2 phases conforming to NEC 430.52 50 hp 250 V at DC 50 hp 600 V at DC | |
| | Heavy duty Heavy application Fusible disconnect None 3 phase 4 600 A 600 V AC/DC NEMA 1 steel 150 hp 480 V at AC 50-60 Hz for 2 phases conforming to NEC 240.6 400 hp 480 V at AC 50-60 Hz for 2 phases conforming to NEC 430.52 200 hp 600 V at AC 50-60 Hz for 2 phases conforming to NEC 240.6 500 hp 600 V at AC 50-60 Hz for 2 phases conforming to NEC 240.6 500 hp 600 V at AC 50-60 Hz for 2 phases conforming to NEC 430.52 50 hp 250 V at DC |

Complementary

| 10 kA H or K | |
|---|--|
| 200 kA R, J or L | |
| H or K | |
| R, J or L | |
| Surface | |
| Lugs | |
| 4-wire | |
| AWG 3/0500 kcmil copper or aluminium | |
| 375 lbf.in (42.37 N.m) (AWG 3/0500 kcmil) | |
| | 200 kA R, J or L H or K R, J or L Surface Lugs 4-wire AWG 3/0500 kcmil copper or aluminium |

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| Depth | 10.13 in (257.30 mm) |
|--------|-----------------------|
| Width | 27.88 in (708.15 mm) |
| Height | 50.31 in (1277.87 mm) |

Environment

| Certifications | UL listed file E2875 |
|----------------|----------------------|

Ordering and shipping details

| Category | 00053 - H&HU SW,NEMA1,400-1200A |
|-----------------------|---------------------------------|
| Discount Schedule | DE1 |
| GTIN | 00785901259152 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 250 lb(US) (113.40 kg) |
| Returnability | No |
| Country of origin | MX |

Offer Sustainability

| Sustainable offer status | Green Premium product |
|-----------------------------|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACh Regulation | REACh Declaration |
| REACh free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information. |
| Environmental Disclosure | Product Environmental Profile |
| PVC free | Yes |
| Halogen content performance | Halogen free plastic parts product |

Contractual warranty

| on the details in a man and y | | |
|-------------------------------|-----------|--|
| Warranty | 18 months | |