Product data sheet Characteristics

HU361DSWC

Safety switch, heavy duty, non fusible, 30A, 600 VAC/VDC, 3 poles, 30 hp, NEMA Type 4, 4X, 5, 304 steel, crouse hinds

Product availability: Non-Stock - Not normally stocked in distribution facility





Price*: 5,888.00 USD



Main

Product	Receptacle Switch	
For Use With	Plug APJ3485 Crouse-Hinds Arktite	
Disconnect Type	Non-fusible disconnect switch	
Phase	3 phase	
Number of Poles	3	
Current rating	30 A	
Voltage Rating	600 V AC 250 V DC	
Enclosure Rating NEMA 3R	NEMA 4/4X/5 stainless steel 304	
Maximum Horse Power Rating	20 hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 30 hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 5 hp 250 V at DC conforming to NEC 430.52	

Complementary

		4
Mounting Type	Surface	<u> </u>
Electrical Connection	Receptacle	ty a
Wire Configuration	4-wire	w w
Wire Size	AWG 12AWG 2 aluminium AWG 14AWG 2 copper	ritended
Tightening torque	45 lbf.in (5.08 N.m) (AWG 6) 40 lbf.in (4.52 N.m) (AWG 8) 35 lbf.in (3.95 N.m) (AWG 14AWG 10)	ration is not i
Depth	5.11 in (129.79 mm)	
Width	10.79 in (274.07 mm)	
Height	16.87 in (428.50 mm)	

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Environment

O : (CC : - C :	
Certifications UL Listed	
Oct till cations OL Listed	

Ordering and shipping details

Category	00118 - H&HU SW,W/C-HINDS RECPT-WC	
Discount Schedule	DE1	
GTIN	00785901077879	
Nbr. of units in pkg.	1	
Package weight(Lbs)	10.00 lb(US) (4.536 kg)	
Returnability	No	
Country of origin	US	

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	16.62 in (42.227 cm)
Package 1 width	5.50 in (13.97 cm)
Package 1 Length	8.87 in (22.542 cm)

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	
Environmental Disclosure	Product Environmental Profile	
PVC free	Yes	

Contractual warranty

Marranti	10 manths	
Vvarranty	18 months	
•		