Product data sheet Characteristics

HU663AWK

Safety switch, heavy duty, non fusible, 100A, 6 poles, 75 hp, 600 VAC/DC, NEMA 12

Product availability: Stock - Normally stocked in distribution facility





Price*: 4,793.00 USD



Main

Product Single Throw Safety Switch Duty Rating Heavy duty Device application Heavy application Disconnect Type Non-fusible disconnect Factory Installed Neutral None Phase 3 phase Number of Poles 6 Current Rating 100 A Voltage Rating 600 V AC Enclosure Rating NEMA 3R/12 galvannealed steel Maximum Horse Power Rating 50 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 75 hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52	
Device application Heavy application Disconnect Type Non-fusible disconnect Factory Installed Neutral None Phase 3 phase Number of Poles 6 Current Rating 100 A Voltage Rating 600 V AC Enclosure Rating NEMA 3R/12 galvannealed steel Maximum Horse Power Rating 50 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52	
Disconnect Type Non-fusible disconnect Factory Installed Neutral None Phase 3 phase Number of Poles 6 Current Rating 100 A Voltage Rating 600 V AC Enclosure Rating NEMA 3R/12 galvannealed steel Maximum Horse Power Rating 50 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52	
Factory Installed Neutral Phase 3 phase Number of Poles 6 Current Rating 100 A Voltage Rating 600 V AC Enclosure Rating NEMA 3R/12 galvannealed steel Maximum Horse Power Rating 50 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52	
Phase 3 phase Number of Poles 6 Current Rating 100 A Voltage Rating 600 V AC Enclosure Rating NEMA 3R/12 galvannealed steel Maximum Horse Power Rating 50 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52	
Number of Poles 6 Current Rating 100 A Voltage Rating 600 V AC Enclosure Rating NEMA 3R/12 galvannealed steel Maximum Horse Power Rating 50 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52	
Current Rating 100 A Voltage Rating 600 V AC Enclosure Rating NEMA 3R/12 galvannealed steel Maximum Horse Power Rating 50 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52	
Voltage Rating 600 V AC Enclosure Rating NEMA 3R/12 galvannealed steel Maximum Horse Power Rating 50 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52	
Enclosure Rating NEMA 3R/12 galvannealed steel Maximum Horse Power Rating 50 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52	
Maximum Horse Power Rating 50 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52	
75 hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52	ot ot see

Complementary

Mounting Type	Surface	
Electrical Connection	Lugs	
Wiring configuration	6-wire	
Wire Size	AWG 12AWG 1/0 aluminium AWG 14AWG 1/0 copper	
Tightening torque	50 lbf.in (5.65 N.m) (AWG 1AWG 3/0) 45 lbf.in (5.08 N.m) (AWG 6AWG 4) 40 lbf.in (4.52 N.m) 0.01 in² (8.367 mm²) (AWG 8) 35 lbf.in (3.95 N.m) 0.000.01 in² (2.065.261 mm²) (AWG 14AWG 10)	
Depth	6.8 in (172.72 mm)	
Width	16.13 in (409.70 mm)	

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Height	20.5 in (520.70 mm)
Net Weight	30.86 lb(US) (14 kg)
Environment	
Certifications	UL listed file E2875
Ordering and shipping details	
Category	00116 - H&HU SW,4&6P,N12,30-200A
Discount Schedule	DE1
GTIN	00785901868378
Nbr. of units in pkg.	1
Package weight(Lbs)	31.5 lb(US) (14.29 kg)
Returnability	Yes
Country of origin	US
Packing Units Unit Type of Package 1	PCE
Package 1 Height	25.90 in (65.786 cm)
Package 1 width	7.10 in (18.034 cm)
Package 1 Length	16.90 in (42.926 cm)
Offer Sustainability Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which
Camorna proposition 05	is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.

Contractual warranty

Environmental Disclosure

PVC free

Oblitacidal Walland		
Warranty	18 months	

Product Environmental Profile

Yes