Product data sheet Characteristics

JDP36250

Circuit breaker, PowerPacT J, unit mount, thermal-magnetic, 250A, 3 pole 14 kA, 600 VAC

Product availability: Non-Stock - Not normally stocked in distribution facility





Price*: 3,749.00 USD



Main

Product or component type

		4
Complementary		4 0
Number of Poles	3P	
Breaking capacity code	D	
Magnetic hold current	1250 A	<u>:</u> :
Magnetic tripping current	2500 A	
Electrical connection	Lugs load Terminal nut line	
Tightening torque	230.12 lbf.in (26 N.m) 0.150.29 in² (95185 mm²) (AWG 3/0350 kcmil)	
Height	7.52 in (191.01 mm)	
Width	4.12 in (104.65 mm)	<u> </u>
Depth	5 in (127.00 mm)	
Continuous current rating	80 %	

Ordering and shipping details

Jul 30, 2021

G. a.c		3
Category	01110 - HD,JD UNIT MT BREAKER/SWITCH	
Discount Schedule	DE2	7
GTIN	00785901947158	
Nbr. of units in pkg.	1	
Package weight(Lbs)	4.84 lb(US) (2.20 kg)	
Returnability	Yes	
Country of origin	MX	

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Circuit breaker

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End of Life Information	
PVC free	Yes	

Contractual warranty

Contractad warranty		
Warranty	18 months	