Product data sheet Characteristics

MPZB15S40F TRANSFORMER MINI POWER ZONE 1PH 15KVA

SQUARE D

Price* : 8,010.00 USD



Main

Vlain		
Product	Sealed Transformer	
Certifications	UL Listed	
Туре	Mini Power-Zone	
Enclosure Code	BB	
Insulation Temperature	365 °F (185 °C)	
Phase	1 phase	
Primary Voltage	480 V	
Secondary Voltage	120/240 V	
Full Capacity Taps	2 5 % FCBN	
Power Rating	15 kVA	
Temperature Rise	115 °C	
Winding Material	Copper	
Interrupt Rating	18 kA	
Circuit Breaker Type	Primary main breaker Secondary main breaker Feeder breaker	
Interior Type	NQ Panelboard interior	
Number of Spaces Available	24	
Number of Circuits	24	
Enclosure Type	NEMA 3R hot-rolled steel	
Ordering and shipping details	S	
Category	16276-MPZ BOLT-ON BRANCH CB	
Discount Schedule	PE2	
GTIN	00785901084327	
Package weight(Lbs)	365.00 lb(US) (165.561 kg)	

Ordering and shipping details		
Category	16276-MPZ BOLT-ON BRANCH CB	
Discount Schedule	PE2	
GTIN	00785901084327	
Package weight(Lbs)	365.00 lb(US) (165.561 kg)	

Returnability	No
Country of origin	US

Packing Units

Package 1 Height	1.21 ft (0.368 m)	
Package 1 width	1.93 ft (0.587 m)	
Package 1 Length	4.39 ft (1.337 m)	

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Nickel (Metallic), which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	
PVC free	Yes	

Contractual warranty

Warranty

18 months

Approximate Dimensions

Product data sheet **Connections and Schema**

MPZB15S40F

Connections and Wiring Diagrams

