Product data sheet Characteristics

NF484L4C

Panelboard interior, NF, main lugs, 400A, Cu bus, 84 pole spaces, 3 phase, 4 wire, 600Y/347VAC max





Price*: 5,991.00 USD



Main

		×
Panelboard Type	Main lugs	9
Branch Circuit Breaker Type	EDB/EDG/EDJ	The state of the s
Busbar Material	Copper	ilit

Complementary

Number of spaces	84
Enclosure Nominal Height	86 in (2184.40 mm)
Enclosure Nominal Width	20 in (508.00 mm)
Enclosure Nominal Depth	5.75 in (146.05 mm) NEMA 1 6.5 in (165.10 mm) NEMA 3R/5/12
Line Rated Current	400 A
[lu] rated interrupted current	65 kA
Wiring configuration	4-wire
Number of Phases	3 phase
Voltage Rating	600Y/347 V AC
Connections - terminals	Lug line AWG 1/0750 kcmil aluminium Lug neutral AWG 1/0750 kcmil aluminium
Tightening torque	274.99300.04 lbf.in (31.0733.90 N.m) 0.080.59 in² (53.48380 mm²) (AWG 1/0750 kcmil) 274.99300.04 lbf.in (31.0733.90 N.m) 0.080.27 in² (53.48177.3 mm²) (AWG 1/0350 kcmil) 549.98 lbf.in (62.14 N.m) 0.080.59 in² (53.48380 mm²) (AWG 1/0750 kcmil) 549.98 lbf.in (62.14 N.m) 0.080.24 in² (53.48152 mm²) (AWG 1/0300 kcmil) 375.01 lbf.in (42.37 N.m) 0.080.59 in² (53.48380 mm²) (AWG 1/0750 kcmil) 375.01 lbf.in (42.37 N.m) 0.080.24 in² (53.48152 mm²) (AWG 1/0300 kcmil)
Height	86 in (2184.40 mm)
Width	10.44 in (265.18 mm)
Net Weight	55.01 lb(US) (24.95 kg)

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Environment

Standards	CSA C22.2
	UL 67

Ordering and shipping details

Category	08350-NF MLO INTERIOR RTA			
Discount Schedule	PE1A			
GTIN	00785901623762			
Package weight(Lbs)	60.00 lb(US) (27.216 kg)			
Returnability	Yes			
Country of origin	US			

Offer Sustainability

Sustainable offer status	Green Premium product		
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov		
REACh Regulation	REACh Declaration		
REACh free of SVHC	Yes		
EU RoHS Directive	Compliant EU RoHS Declaration		
Toxic heavy metal free	Yes		
Mercury free	Yes		
RoHS exemption information	Yes		
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)		
Environmental Disclosure	Product Environmental Profile		

Contractual warranty

	,			
Warranty	•	18 months		