Product data sheet Characteristics

QO2L30TTS

QO LoadCenter, main lug, 30 A, 120 V, 1 PH, 2 W, 2 SP, NEMA1, gnd bar, surface cover

Product availability: Non-Stock - Not normally stocked in distribution facility

SQUARE D

Price*: 51.00 USD



Main

Man		
Marketing Trade Name	QO	-
Product Type	Load Center	
Cover Type	Surface cover	***************************************

Complementary

Tightening Torque	Main lugs 35 lb.in, AWG 14AWG 10, aluminium/copper Main lugs 35 lb.in, AWG 12AWG10, aluminium/copper	
Load Center Type	Main lugs	
Rated Current	30 A	
Number of Spaces	2	
Max Short Circuit Current Rating	10 kA	
Maximum Number of Single Pole Circuits	2	
Maximum Number of Tandem Breakers	0	
Number of Phases	1 phase	
Voltage Rating	120/240 V AC	
Wire Size	AWG 12AWG 10 aluminium AWG 14AWG 10 copper	
Ground Bar	Grounding bar (factory installed)	
Electrical Connection	Lugs	
Wiring Configuration	2-wire	
Busbar Material	Tin plated aluminium busbar	
Enclosure Material	Welded sheet steel	
Surface Finish	Baked enamel Gray	-
Box Number	1	F

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Height	6.73 in (171 mm)	
Width	3.82 in (97 mm)	
Environment		
Enclosure Rating	NEMA 1 indoor	
Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)	
Product Certifications	CSA	
Ordering and shipping details		
Category	00101 - QO 1PH LC,2-8CKT,NEMA 1,3R	
Discount Schedule	DE3A	
GTIN	00785901785088	
Nbr. of units in pkg.	1	
Package weight(Lbs)	1.87 lb(US) (0.85 kg)	
Returnability	No	
Country of origin	MX	
Packing Units Package 1 Height	3.70 in (9.398 cm)	
Package 1 width	4.00 in (10.160 cm)	
Package 1 Length	7.00 in (17.780 cm)	
Offer Sustainability		
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)	

Contractual	warranty

Contractual warranty		
Warranty	18 months	