Product data sheet Characteristics

QO2L70RB

Load center, QO, 1 phase, 2 spaces, 2 circuits, 70A fixed main lugs, NEMA3R, UL

Product availability: Stock - Normally stocked in distribution facility

SQUARE D



Price*: 131.00 USD



Main

Wilder	
Marketing Trade Name	QO
Product Type	Load Center
Enclosure Type	Weatherproof enclosure
Cover Type	Surface cover

Complementary

Marketing Trade Name QO Product Type Load Center Enclosure Type Weatherproof enclosure Cover Type Surface cover Complementary Load Center Type Main lugs Rated Current 70 A Number of Spaces 2 Max Short Circuit Current Rating 10 kA Maximum Number of Single Pole 2 Circuits Maximum Number of Tandem 0 Breakers 1 phase 120/240 V AC Ground Bar Grounding bar (ordered separately) Electrical Connection Lugs Wiring Configuration 3-wire Busbar Material Tin plated aluminium busbar Enclosure Material Welded galvannealed steel Height 9.29 in (236 mm) Write is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.	The second secon		
Marketing Trade Name QO Product Type Load Center Enclosure Type Weatherproof enclosure Cover Type Surface cover Complementary Load Center Type Main lugs Rated Current 70 A Number of Spaces 2 Max Short Circuit Current Rating 10 kA Maximum Number of Single Pole 2 Circuits Maximum Number of Tandem 0 Breakers 1 phase 120/240 V AC Ground Bar Grounding bar (ordered separately) Electrical Connection Lugs Wiring Configuration 3-wire Busbar Material Tin plated aluminium busbar Enclosure Material Welded galvannealed steel Height 9.29 in (236 mm) Write is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.			
Product Type Load Center Enclosure Type Weatherproof enclosure Cover Type Surface cover Complementary Load Center Type Main lugs Rated Current 70 A Number of Spaces 2 Max Short Circuit Current Rating 10 kA Maximum Number of Single Pole Circuits Maximum Number of Tandem Breakers Number of Phases 1 phase Voltage Rating 120/240 V AC Ground Bar Grounding bar (ordered separately) Electrical Connection Lugs Wiring Configuration 3-wire Busbar Material Tin plated aluminium busbar Enclosure Material Welded galvannealed steel Height 9.29 in (236 mm) Wridth 4.76 in (121 mm) Depth 3.94 in (100 mm)	Main		
Enclosure Type Weatherproof enclosure Cover Type Surface cover Complementary Load Center Type Main lugs Rated Current 70 A Number of Spaces 2 Max Short Circuit Current Rating 10 kA Maximum Number of Single Pole 2 Circuits Maximum Number of Tandem 0 Breakers Number of Phases 1 phase Voltage Rating 120/240 V AC Ground Bar Grounding bar (ordered separately) Electrical Connection Lugs Wiring Configuration 3-wire Busbar Material Tin plated aluminium busbar Enclosure Material Welded galvannealed steel Height 9.29 in (236 mm) Width 4.76 in (121 mm) Depth 3.94 in (100 mm)		***	
Complementary Load Center Type Main lugs Rated Current 70 A Number of Spaces 2 Max Short Circuit Current Rating 10 kA Maximum Number of Single Pole Circuits Maximum Number of Tandem 0 Breakers Number of Phases 1 phase Voltage Rating 120/240 V AC Ground Bar Grounding bar (ordered separately) Electrical Connection Lugs Wiring Configuration 3-wire Busbar Material Tin plated aluminium busbar Enclosure Material Welded galvannealed steel Height 9.29 in (236 mm) Width 4.76 in (121 mm) Depth 3.94 in (100 mm)			
Complementary Load Center Type Main lugs Rated Current 70 A Number of Spaces 2 Max Short Circuit Current Rating 10 kA Maximum Number of Single Pole 2 Circuits Maximum Number of Tandem 0 Breakers Number of Phases 1 phase Voltage Rating 120/240 V AC Ground Bar Grounding bar (ordered separately) Electrical Connection Lugs Wiring Configuration 3-wire Busbar Material Tin plated aluminium busbar Enclosure Material Welded galvannealed steel Height 9.29 in (236 mm) Width 4.76 in (121 mm) Depth 3.94 in (100 mm)		Weatherproof enclosure	
Load Center Type Main lugs Rated Current 70 A Number of Spaces 2 Max Short Circuit Current Rating 10 kA Maximum Number of Single Pole Circuits 2 Maximum Number of Tandem Breakers 0 Breakers 1 phase Voltage Rating 120/240 V AC Ground Bar Grounding bar (ordered separately) Electrical Connection Lugs Wiring Configuration 3-wire Busbar Material Tin plated aluminium busbar Enclosure Material Welded galvannealed steel Height 9.29 in (236 mm) Width 4.76 in (121 mm) Depth 3.94 in (100 mm)	Cover Type	Surface cover	
Load Center Type Main lugs Rated Current 70 A Number of Spaces 2 Max Short Circuit Current Rating 10 kA Maximum Number of Single Pole Circuits Maximum Number of Tandem Preakers Number of Phases 1 phase Voltage Rating 120/240 V AC Ground Bar Grounding bar (ordered separately) Electrical Connection Lugs Wiring Configuration 3-wire Busbar Material Tin plated aluminium busbar Enclosure Material Welded galvannealed steel Height 9.29 in (236 mm) Width 4.76 in (121 mm) Depth 3.94 in (100 mm)			
Rated Current 70 A Number of Spaces 2 Max Short Circuit Current Rating 10 kA Maximum Number of Single Pole 2 Circuits Maximum Number of Tandem 0 Breakers Number of Phases 1 phase Voltage Rating 120/240 V AC Ground Bar Grounding bar (ordered separately) Electrical Connection Lugs Wiring Configuration 3-wire Busbar Material Tin plated aluminium busbar Enclosure Material Welded galvannealed steel Height 9.29 in (236 mm) Width 4.76 in (121 mm) Depth 3.94 in (100 mm)	<u> </u>		
Number of Spaces 2 Max Short Circuit Current Rating 10 kA Maximum Number of Single Pole 2 Circuits Maximum Number of Tandem 0 Breakers Number of Phases 1 phase Voltage Rating 120/240 V AC Ground Bar Grounding bar (ordered separately) Electrical Connection Lugs Wiring Configuration 3-wire Busbar Material Tin plated aluminium busbar Enclosure Material Welded galvannealed steel Height 9.29 in (236 mm) Width 4.76 in (121 mm) Depth 3.94 in (100 mm)	Load Center Type	Main lugs	
Max Short Circuit Current Rating 10 kA Maximum Number of Single Pole Circuits Maximum Number of Tandem 0 Breakers Number of Phases 1 phase Voltage Rating 120/240 V AC Ground Bar Grounding bar (ordered separately) Electrical Connection Lugs Wiring Configuration 3-wire Busbar Material Tin plated aluminium busbar Enclosure Material Welded galvannealed steel Height 9.29 in (236 mm) Width 4.76 in (121 mm) Depth 3.94 in (100 mm)	Rated Current	70 A	
Maximum Number of Single Pole Circuits Maximum Number of Tandem Description 1 phase 1	Number of Spaces	2	
Circuits Maximum Number of Tandem Breakers 0 Number of Phases 1 phase Voltage Rating 120/240 V AC Ground Bar Grounding bar (ordered separately) Electrical Connection Lugs Wiring Configuration 3-wire Busbar Material Tin plated aluminium busbar Enclosure Material Welded galvannealed steel Height 9.29 in (236 mm) Width 4.76 in (121 mm) Depth 3.94 in (100 mm) * Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.	Max Short Circuit Current Rating	10 kA	
Breakers Number of Phases 1 phase Voltage Rating 120/240 V AC Ground Bar Grounding bar (ordered separately) Electrical Connection Lugs Wiring Configuration 3-wire Busbar Material Tin plated aluminium busbar Enclosure Material Welded galvannealed steel Height 9.29 in (236 mm) Width 4.76 in (121 mm) Depth 3.94 in (100 mm) * Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.		2	
Voltage Rating 120/240 V AC Ground Bar Grounding bar (ordered separately) Electrical Connection Lugs Wiring Configuration 3-wire Busbar Material Tin plated aluminium busbar Enclosure Material Welded galvannealed steel Height 9.29 in (236 mm) Width 4.76 in (121 mm) Depth 3.94 in (100 mm)		0	
Ground Bar Grounding bar (ordered separately) Electrical Connection Lugs Wiring Configuration 3-wire Busbar Material Tin plated aluminium busbar Enclosure Material Welded galvannealed steel Height 9.29 in (236 mm) Width 4.76 in (121 mm) Depth 3.94 in (100 mm)	Number of Phases	1 phase	
Electrical Connection Lugs Wiring Configuration 3-wire Busbar Material Tin plated aluminium busbar Enclosure Material Welded galvannealed steel Height 9.29 in (236 mm) Width 4.76 in (121 mm) Depth 3.94 in (100 mm)	Voltage Rating	120/240 V AC	
Wiring Configuration 3-wire Busbar Material Tin plated aluminium busbar Enclosure Material Welded galvannealed steel Height 9.29 in (236 mm) Width 4.76 in (121 mm) Depth 3.94 in (100 mm) * Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.	Ground Bar	Grounding bar (ordered separately)	
Busbar Material Enclosure Material Welded galvannealed steel Height 9.29 in (236 mm) Width 4.76 in (121 mm) Depth 3.94 in (100 mm)	Electrical Connection	Lugs	
Enclosure Material Height 9.29 in (236 mm) Width 4.76 in (121 mm) Depth 3.94 in (100 mm) * Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.	Wiring Configuration	3-wire	
Height 9.29 in (236 mm) Width 4.76 in (121 mm) Depth 3.94 in (100 mm) * Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.	Busbar Material	Tin plated aluminium busbar	
Width 4.76 in (121 mm) Depth 3.94 in (100 mm) * Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.	Enclosure Material	Welded galvannealed steel	_
Depth 3.94 in (100 mm) * Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.	Height	9.29 in (236 mm)	
* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.	Width	4.76 in (121 mm)	
	Depth	3.94 in (100 mm)	
	Price is "List Price" and may be subject to a trade	discount – check with your local distributor or retailer for actual price.	

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Environment

Enclosure Rating	NEMA 3R outdoor
Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)
Product Certifications	CULus

Ordering and shipping details

Category	00156 - CANADIAN LOAD CTRS
Discount Schedule	DE3A
GTIN	00785901965701
Nbr. of units in pkg.	1
Package weight(Lbs)	5.09 lb(US) (2.31 kg)
Returnability	Yes
Country of origin	MX

Packing Units

r doming ormo	
Unit Type of Package 1	PCE
Package 1 Height	4.80 in (12.192 cm)
Package 1 width	5.90 in (14.986 cm)
Package 1 Length	11.10 in (28.194 cm)
Unit Type of Package 2	PAL
Number of Units in Package 2	213
Package 2 Weight	1099.08 lb(US) (498.534 kg)
Package 2 Height	40.00 in (101.6 cm)
Package 2 width	36.00 in (91.44 cm)
Package 2 Length	48.00 in (121.92 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile

Contractual warranty

oonaddan warang		
Warranty	18 months	