Product data sheet Characteristics

QO3100BNRB

Load center enclosure, QO, 3 phase, 3 spaces, used with 100A breaker, NEMA3R, UL

Product availability: Stock - Normally stocked in distribution facility

SQUARE D

Price*: 207.00 USD



Main

Marketing Trade Name	QO	
Product Type	Enclosure	
Enclosure Type	Weatherproof enclosure	
Cover Type	Surface cover	

Complementary

Complementary	
Tightening Torque	35 lb.in, AWG 14AWG 10, copper 35 lb.in, AWG 12AWG 10, aluminium Main lugs 40 lb.in, AWG 8AWG 4, aluminium/copper Main lugs 50 lb.in, AWG 3AWG 2, aluminium/copper Main lugs 35 lb.in, AWG 14AWG 10, copper Main lugs 35 lb.in, AWG 12AWG 10, aluminium
Load Center Type	Main lugs
Rated Current	100 A
Number of Spaces	3
Max Short Circuit Current Rating	22 kA
Maximum Number of Tandem Breakers	0
Number of Phases	3 phase
Ground Bar	Grounding bar (ordered separately)
Electrical Connection	Lugs
Busbar Material	Tin plated copper
Enclosure Material	Welded galvannealed steel
Surface Finish	Baked enamel Gray
Box Number	10R
Height	13.19 in (335 mm)

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Width	6.93 in (176 mm)				
Environment					
Enclosure Rating	NEMA 3R outdoor				
Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)				
Product Certifications UL Listed CSA					
Ordering and shipping details					
Category	00023 - QO,Q2L 3P ENCL & BREAKERS				
Discount Schedule	DE2				
GTIN	00785901051770				
Nbr. of units in pkg.	1				
Package weight(Lbs)	8.09 lb(US) (3.67 kg)				
Returnability Yes					
Country of origin	MX				
Packing Units					
Unit Type of Package 1	PCE				
Package 1 Height	5.00 in (12.7 cm)				
Package 1 width	8.11 in (20.6 cm)				
Package 1 Length	14.49 in (36.8 cm)				
Offer Sustainability					
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov				
REACh Regulation	REACh Declaration				
REACh free of SVHC	Yes				
EU RoHS Directive	Compliant EU RoHS Declaration				
Toxic heavy metal free	Yes				
Mercury free	Yes				

~ · · ·	
Contractual	l warrantv

China RoHS Regulation


RoHS exemption information

Warranty	18 months

China RoHS declaration
Pro-active China RoHS declaration (out of China RoHS legal scope)

Yes


Dimensions



			KN	OCKOUT	S		
I	SYMB0L	А	В	С	D	Е	F
	IN	.50	.75	1.00	1.25	1.50	2.00
	MM	13	19	25	32	38	51

All dimensions are approximate. Also see technical documentation.

Wiring Diagram



QO3100BNF QO3100BNS QO3100BNRB