

Product data sheet

Characteristics

QO4L100S

Load center, QO, 1 phase, 4 spaces, 4 circuits, 100A convertible main lugs, NEMA1, surface cover, CSA

Product availability : Stock - Normally stocked in distribution facility



Price* : 93.00 USD



Main

Marketing Trade Name	QO
Product Type	Load Center
Cover Type	Surface cover

Complementary

Tightening Torque	Cover 20 lb.in
Load Center Type	Main lugs
Rated Current	100 A
Number of Spaces	4
Max Short Circuit Current Rating	10 kA
Maximum Number of Single Pole Circuits	4
Maximum Number of Tandem Breakers	0
Number of Phases	1 phase
Voltage Rating	120/240 V AC
Ground Bar	Grounding bar (ordered separately)
Electrical Connection	Lugs
Wiring Configuration	3-wire
Busbar Material	Tin plated aluminium busbar
Height	12.56 in (319 mm)
Width	8.90 in (226 mm)
Depth	3.74 in (95 mm)

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Environment

Enclosure Rating	NEMA 1 indoor
Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)
Product Certifications	CSA

Ordering and shipping details

Category	00156 - CANADIAN LOAD CTRS
Discount Schedule	DE3A
GTIN	00785901207764
Nbr. of units in pkg.	1
Package weight(Lbs)	7.73 lb(US) (3.51 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Package 1 Height	4.50 in (11.430 cm)
Package 1 width	11.00 in (27.940 cm)
Package 1 Length	14.50 in (36.830 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)

Contractual warranty

Warranty	18 months
----------	-----------