

Product data sheet

Characteristics

QOB330EPE5237

Mini circuit breaker, QO, 30A, 3 pole, 240 VAC,
10 kA, 100mA grd fault B, bolt on mount, ring

Product availability : Non-Stock - Not normally stocked in distribution facility



Price* : 1,320.00 USD



Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	30 A
Voltage Rating	240 V AC
Mounting Type	Bolt-on
Number of Poles	3P
Circuit Breaker Type	Ground fault protecting class B 100 mA
Ratings	Not rated
Electrical Connection	Ring tongue

Complementary

Interrupt Rating	10 kA 240 V AC 50/60 Hz
Number of Panel Spaces	2
Wire Size	AWG 14...AWG 8 copper AWG 12...AWG 8 aluminium
Tightening Torque	40.71 lbf.in (4.6 N.m) 0.00...0.02 in ² (2.5...10 mm ²) (AWG 16...AWG 14) 40.71 lbf.in (4.6 N.m) 0.01...0.03 in ² (4...20 mm ²) (AWG 12...AWG 4)
Height	4.12 in (104.65 mm)
Width	2.25 in (57.15 mm)
Depth	2.91 in (73.91 mm)

Environment

Certifications	UL Listed CSA
Ambient Rating	104 °F (40 °C)

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Jul 30, 2021

Ordering and shipping details

Category	00910 - QO-EPD,QOB-EPD BREAKERS
Discount Schedule	DE2A
Nbr. of units in pkg.	15
Package weight(Lbs)	15 lb(US) (6.80 kg)
Returnability	No

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty	18 months
----------	-----------