## Product data sheet Characteristics

## RXZE2M114

Zelio, plugin relay socket, mixed contact, 10 A, 250 V, screw clamp, for RXM2 or RXM4 relays

Product availability: Stock - Normally stocked in distribution facility



Price\*: 6.10 USD



#### Main

Harmony Electromechanical Relays Harmony Timer Relays	
Socket	
Mixed	
Plug-in relay RXM 2 C/O Plug-in relay RXM 4 C/O	
Flat	
RXZ	
10	
	Harmony Timer Relays  Socket  Mixed  Plug-in relay RXM 2 C/O Plug-in relay RXM 4 C/O  Flat  RXZ

#### Complementary

Complementary		
[lth] conventional free air thermal current	10 A	
[Ue] rated operational voltage	< 250 V	
Connections - terminals	Screw clamp terminals, 1 x 0.251 x 1 mm² AWG 22AWG 17) flexible with cable end Screw clamp terminals, 2 x 0.252 x 1 mm² AWG 22AWG 17) flexible with cable end Screw clamp terminals, 1 x 0.51 x 1.5 mm² AWG 20AWG 16) solid without cable end Screw clamp terminals, 2 x 0.52 x 1.5 mm² AWG 20AWG 16) solid without cable end	
Tightening torque	< 1 N.m M3	
Fixing mode	By screw panel) Clip-on 35 mm symmetrical DIN rail)	70000
Marking	CE	<u>.</u>
Width	1.18 in (30 mm)	.9
Net Weight	0.11 lb(US) (0.048 kg)	

<sup>\*</sup> Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

### Environment

Standards	IEC 61984
Product certifications	UL CSA Lloyd's
Ambient air temperature for storage	-40185 °F (-4085 °C)
Ambient air temperature for operation	-40131 °F (-4055 °C)
IP degree of protection	IP20 conforming to EN/IEC 60529
Dielectric strength	2500 V

## Ordering and shipping details

Category	21128 - ZELIO ICE CUBE RELAY ACCESSORIES
Discount Schedule	CP2
GTIN	03389119404242
Nbr. of units in pkg.	1
Package weight(Lbs)	1.83 oz (52 g)
Returnability	Yes
Country of origin	CN

### Packing Units

r acking office	
Unit Type of Package 1	PCE
Package 1 Height	1.53 in (38.96 mm)
Package 1 width	1.18 in (30.05 mm)
Package 1 Length	3.24 in (82.18 mm)
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	19.72 oz (559 g)
Package 2 Height	2.83 in (7.2 cm)
Package 2 width	3.35 in (8.5 cm)
Package 2 Length	6.10 in (15.5 cm)
Unit Type of Package 3	S03
Number of Units in Package 3	200
Package 3 Weight	25.62 lb(US) (11.621 kg)
Package 3 Height	11.81 in (30 cm)
Package 3 width	11.81 in (30 cm)
Package 3 Length	15.75 in (40 cm)

## Offer Sustainability


Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile

WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Contractual warranty	
Warranty	18 months

# Product data sheet Dimensions Drawings

## Socket

## Socket with Mixed Contact Terminals and Clamp Terminals



- 1 Relay
- 2 Protection Module
- 3 Carriage Stirrup