



| SPECIFICATIONS | |
|---|---|
| OPERATING VOLTAGE | 10-30 VDC |
| RIPPLE | ≤10% |
| DIFFERENTIAL TRAVEL (HYSTERESIS) | 3-15% (5% TYPICAL) |
| VOLTAGE DROP ACROSS CONDUCTING SENSOR | ≤1.8 V at 200 mA |
| OUTPUT FUNCTION | NORMALLY OPEN 3-WIRE DC SELF-CONTAINED |
| SHORT-CIRCUIT PROTECTED | YES |
| TRIGGER CURRENT FOR OVERLOAD PROTECTION | ≥220 mA |
| CONTINUOUS LOAD CURRENT | ≤200 mA |
| OFF-STATE (LEAKAGE) CURRENT | ≤0.1 mA |
| NO-LOAD CURRENT | ≤15 mA |
| TIME DELAY BEFORE AVAILABILITY | ≤8 ms |
| POWER-ON EFFECT | PER IEC 947-5-2 |
| REVERSE POLARITY PROTECTION | INCORPORATED |
| WIRE-BREAK PROTECTION | INCORPORATED |
| PROTECTION AGAINST TRANSIENTS | Per EN 60947-5-2 |
| OPERATING TEMPERATURE (10% DRIFT) | -25°C to +70°C (-13°F to +158°F) |
| OPERATING TEMPERATURE (15% DRIFT) | -30°C to +85°C (-22°F to +185°F) |
| ENCLOSURE | MEETS NEMA 1, 3, 4, 6, 13 AND IEC IP68 |
| SHOCK | 30 g, 11 ms |
| VIBRATION | 55 Hz, 1 mm AMPLITUDE (IN ALL 3 PLANES) |
| LED FUNCTION | YELLOW: OUTPUT ENERGIZED |
| RATED OPERATING DISTANCE(Sn) | 15 mm = .591" (NOMINAL) |
| SWITCHING FREQUENCY | 2500 Hz |
| REPEATABILITY | ≤2% of RATED OPERATING DISTANCE |
| EMBEDDABLE (SHIELDED) | YES |

SOURCE DRAWING - FOR REFERENCE ONLY

RELATED DOCUMENTS 3RD ANGLE PROJECTION THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS NOTES: 3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 1. MATERIAL: 2. (763) 553-7300 DOCUMENT WITHOUT WRITTEN PERMISSION STAINLESS STEEL BARREL 3. (763) 553-0708 fax STAINLESS STEEL CONNECTOR PROHIBITED. www.turck.us STAINLESS STEEL LOCKNUTS DATE 10/29/01 MATERIAL DESCRIPTION RDS SEE NOTES BI15-EM30H-AN6X-H1141 2. GLASS-FILLED THERMOSET PLASTIC SENSING FACE. ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY APVD SCALE 1 = 2.0UNIT OF MEASUREMENT IDENTIFICATION NO. REV FINISH CONTACT TURCK FOR MORE INFORMATION INCH [MILLIMETER] 4618692 UPDATE ID NUMBER PER HARMONIZATION PROJECT СВМ 11/06/17 DESCRIPTION BY DATE ECO NO. DO NOT SCALE THIS DRAWING FILE: 4618692 SHEET 1 OF 1