


FEMALE END VIEW

1 2

M16 connector

 M16 connector

SPECIFICATIONS	
HOUSING MATERIAL/COLOR	GLASS FILLED NYLON or PVC/BLACK
CONTACT MATERIAL/PLATING	BRASS or TeCU/GOLD
COUPLING NUT MATERIAL/PLATING	BRASS/NICKEL
RATED CURRENT [A]	18.0 A
RATED VOLTAGE [V]	600 V
MAXIMUM WIRE SIZE	12 AWG
TERMINATION METHOD	SCREW TERMINAL
TEMPERATURE RATING	-40°C to +90°C (-40°F to +194°F)
PROTECTION CLASS	IP 67/NEMA 6P
CABLE GRIP RANGE	PG 11 = 8-11mm

WIRE SIDE VIEW
OF CONTACT HOLDER
TO SHOW LABEL DETAILS

WHITE

BLACK

1

2

TURNS


(SCALE 2:1)

69.0 [2.72] REF.

Ø19.0 [0.75]

M16x0.75

SOURCE DRAWING - FOR REFERENCE ONLY



- BLACK

WHITE



(SCALE 2:1)



CAUTION:

**⚠ RISK OF ELECTRICAL SHOCK
DO NOT DISCONNECT UNDER LOAD**

SOURCE DRAWING - FOR REFERENCE ONLY

RELATED DOCUMENTS 1. 2. 3. 4.	3RD ANGLE PROJECTION		THIS DRAWING IS PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.	<div>TURCK INC <i>High Technology Sensors and Automation Controls</i></div>		3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax turck.com			
MATERIAL	ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY		DRFT	RDS	DATE	12/02/08	DESCRIPTION	BK 22-0	
SEE SPECIFICATIONS			DSGN		SCALE	1=1.0			
FINISH			CONTACT TURCK FOR MORE INFORMATION	<div>UNIT OF MEASUREMENT MILLIMETER [INCH]</div>	IDENTIFICATION NO.				REV
SEE SPECIFICATIONS					U2-14091				B
				FILE: U2-14091			SHEET 1 OF 1		