


NOTES:


REV DESCRIPTION

H ADD SPECS & UPDATE SCREW LENGTH


SPECIFICATIONS				
CONTACT CARRIER MATERIAL	NYLON OR TPU			
CONTACT MATERIAL/PLATING	BRASS/GOLD			
RATED CURRENT [A]	4.0 A			
RATED VOLTAGE [V]	250 V			
HOUSING MATERIAL	BRASS/NICKEL			
CONDUCTORS	PCB PINS			
TEMPERATURE RATING	-30°C to +80°C (-22°F to +176°F)			
PROTECTION CLASS	MEETS NEMA 1,3,4,6P AND IEC IP68			
MAX BOARD THICKNESS	2mm			



1. FOR OTHER RIGHT ANGLE CONNECTORS, ROTATE BOARD LAYOUT TO DESIRED ORIENTATION OR ROTATE 5-HOLE PINOUT IN INCREMENTS OF 60°.



BOARD LAYOUT SCALE 2=1



RIGHT ANGLE CONNECTOR ORIENTATION

## SOURCE DRAWING - FOR REFERENCE ONLY

			RELATED DOCUMENTS  1. INSERT SHEET 10240122  2.  3.  4.	3RD ANGLE PROJECTION	THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.		RCI	(763) 5 (763) 5		55441 769 00 08 fax
ARD LAYOUT TO			MATERIAL SEE SPECIFICATIONS	SEE SPECIFICATIONS  ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY		DATE 08/14/98 SCALE 1=1.0	description FS 5			
		O°.	FINISH		UNIT OF MEASUREMENT  MILLIMETER [ INCH ]		IDENTIFICATION NO.			REV
NF BY	08/01/19 DATE	500000000281 ECO NO.	SEE SPECIFICATIONS	CONTACT TURCK FOR MORE INFORMATION	DO NOT SCALE THIS DRAWING		U FILE: U1132-0	1132-0	SHEET	1 OF 1