



MATERIALS	
BODY:	BLACK POLYAMIDE
CONTACTS:	GOLD PLATED COPPER ALLOY
CABLE SEAL:	NBR
INSERT:	YELLOW PVC
COUPLING:	NICKEL PLATED BRASS
RATINGS	
AMDC.	44AWC 40A may
AMPS:	14AWG - 18A max
	16AWG - 13A max
	18AWG - 10A max
	20-22AWG - 4A max
VOLTS:	600V MAX
SEAL:	IP67
CABLE RANGE:	14AWG - 22AWG
	0.20" - 0.51" (5mm - 13mm) OD
APPROVALS	(14 - 20AWG only)
US:	UL LISTED
CANADA:	C-UL LISTED

Voltage rating is 600V or the rating of the cable, whichever is less.

Connections made via screw terminals.

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
MENCOM CORPORATION. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
MENCOM CORPORATION IS
PROHIBITED.

	UNLESS OTHERWISE SPECIFIED:		NAME	
	DIMENSIONS ARE IN INCHES	DRAWN	BEM	
	AND [MM]	CHECKED		TI
		ENG APPR.		
		MFG APPR.		
		Q.A.		
	MATERIAL	COMMENTS:		SI
	DO NOT SCALE DRAWING			SC

DLIVI							
	TITLE	:					
	SIZE	SIZE DWG. NO.				REV	
	B MIN-3FP-FW SCALE: 2:1 WEIGHT:		P-FW		C		
			WEIGHT:		SHEE	T 1 OF 1	

MENCOM CORPORATION

8 / 6 5 4 3 2