

MALE END VIEW

M23 connector

FEMALE END VIEW

TURCK IAS

SPECIFICATIONS	
CONTACT CARRIER MATERIAL/COLOR	NYLON OR TPU/BLACK
CONTACT MATERIAL/PLATING	BRASS/GOLD
HOUSING MATERIAL/PLATING	BRASS/NICKEL (P1)
HOUSING MATERIAL/COLOR	NYLON/YELLOW
O-RING MATERIAL	VITON
RATED CURRENT [A]	4 AMPS PER PORT, 9 AMPS TOTAL
RATED VOLTAGE [V]	10-48 V
TEMPERATURE RANGE	-40°C to +80°C (-40°F to +176°F)
PROTECTION CLASS	MEETS IEC IP67, ONLY WHEN ALL RECEPTACLES ARE COVERED WITH PLUGS OR CONNECTED

4x LED YELLOW (OUTPUT)

LED GREEN (POWER)

5x SNAP LABEL

3x $\varnothing 4.3$ [$\varnothing 0.17$] CLEARANCE HOLE FOR #8 OR M4 SCREW

P1

M23x1

NOTES:

1. MATING CORDSET CKM-12-7-* SOLD SEPERATLY.

CLOSURE CAPS (2 INCLUDED)

RELATED DOCUMENTS	3RD ANGLE PROJECTION	THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.	3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax turck.com	
1.		DRFT RJP	DATE 11/16/95	DESCRIPTION VB 40-N7X5-CS12
2.			SCALE 1=1.5	
3.	ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY	UNIT OF MEASUREMENT MILLIMETER [INCH]	IDENTIFICATION NO. U7009-4	REV D
4.				
MATERIAL SEE SPECIFICATIONS	DO NOT SCALE THIS DRAWING	FILE: U7009-4		
FINISH SEE SPECIFICATIONS		SHEET 1 OF 1		