





# NAN (M8) Series Field Wireable Plugs

3 & 4 Conductor NAN Series Field Wireable Plugs, 22-24AWG



Field Wireable Plugs | Axial Piercing | 60V, 3 amps | IP67 Rating




| # of Poles | Male Faceview                                                                     | Wire AWG Rating        | Cable O.D. Range | Male Plugs   |                | Female Plugs |                |
|------------|-----------------------------------------------------------------------------------|------------------------|------------------|--------------|----------------|--------------|----------------|
|            |                                                                                   |                        |                  | Straight     | Right Angle    | Straight     | Right Angle    |
| 3          |  | 18-24 AWG<br>60V<br>3A | 4-5 mm           | NAN-T-3MP-FW | NAN-T-3MP-FW-R | NAN-T-3FP-FW | NAN-T-3FP-FW-R |
| 4          |  | 18-24 AWG<br>60V<br>3A | 4-5 mm           | NAN-T-4MP-FW | NAN-T-4MP-FW-R | NAN-T-4FP-FW | NAN-T-4FP-FW-R |

**J**  
NAN (M8) Series


**Specifications:**  
 Body: Oil Resistant Black PVC  
 Insulator: Polyamide  
 Contacts: Copper Alloy with Gold Plating  
 O-Rings: NBR  
 Coupling Nut: Nickel Plated ZnAl  
 Grommet: NBR  
 Connection: Axial Piercing  
 Temperature: -25°C to +90°C (-13°F to +194°F)

**Straight**




Male Plug


**Right Angle**



Male Plug



Female Plug



Female Plug